



Firma: G Store & Repair doo
Adresa: Bul.Mihajla Pupina 10z/3
Telefon: 011 785 66 66
Fax:
PIB: 112029009
E-mail: office@gstore.rs

DAHUA IPC-HDW2449TM-S-IL-0280B AI IP 4MP

eyeball kamera sa hibridnim iluminatorima;

Wizsense serija;



Šifra: 102393

Kategorija proizvoda: Kamere IP

Proizvođač: DAHUA

Cena: 22.592 rsd.

AI IP eyeball kamera 4MP sa hibridnim iluminatorima

1/2.9" CMOS, progresivno skeniranje (2688x1520 piksela)

Starlight

Osetljivost 0.008Lux /F1.6 (kolor), 0.0008Lux /F1.6 (C/B), 0Lux (IC aktivan.)

IC LE dioda dometa cca. 30m

Beli LE dometa cca. 30m

Objektiv 2.8mm (Vidni ugao 95 horizontalno), 3.6mm opciono (78)

Fiksni iris

True D/N funkcija (ICR)

BLC /HLC /WDR 120dB

3D DNR

ROI (do 4 zone)

Masking (do 4 zone)

AI Analitika - detekcija prelaska definisane linije i ulaska/izlaska u definisani region (uz detekciju ljudi i vozila) - SMD+

Detekcija pokreta (do 4 zone)

Smart H.265+ /H.265 /Smart H.264+ /H.264 /H.264H /H.264B /MJPEG kompresija

Rezolucije 4M (2688 × 1520 i 2560 × 1440) /3M (2304 × 1296) /1080P /1.3M /720P /D1 /VGA /CIF

Dual Stream

Do 20fps u 2688 × 1520, do 25-30fps u 2560 × 1440 i nižim rezolucijama

RJ-45 (10/100Base-T) mrežni port

Protokoli IPv4, IPv6, HTTP, TCP, UDP, ARP, RTP, RTSP, RTCP, RTMP, SMTP, FTP, SFTP, DHCP, DNS, DDNS, NTP, Multicast, ICMP, IGMP

Interoperabilnost: ONVIF (Profile S/Profile T), CGI, P2P, Milestone

SDK i API

Skladištenje: FTP, SFTP, MicroSD (do 256 GB)

Inkorporiran mikrofon

Potrebno napajanje 12Vdc ili PoE (802.3af)

Potrošnja 5.2W, Wide voltage support ±30%

Dimenzije 99.1 mm × 121.9 mm

Masa 0.46kg

IP67 sertifikovana

Radna temp. -40C~+60C

CE-LVD: EN 62368-1, CE-EMC: Electromagnetic Compatibility Directive 2014/30/EU, FCC: 47 CFR FCC Part 15, Subpart B