



Firma: G Store & Repair doo  
Adresa: Bul.Mihajla Pupina 10z/3  
Telefon: 011 785 66 66  
Fax:  
PIB: 112029009  
E-mail: [office@gstore.rs](mailto:office@gstore.rs)

---

## LAN Router TP-LINK TL-WR841N Wireless (2)

Šifra: 105041

Kategorija proizvoda: Ruteri

Proizvođač: TP-Link

**Cena: 2.971 rsd.**



### HARDWARE FEATURES

<b>Interface</b>	4 10/100Mbps LAN PORTS 1 10/100Mbps WAN PORT
<b>Button</b>	Quick Setup Security Button Reset Button
<b>External Power Supply</b>	9VDC / 0.6A
<b>Wireless Standards</b>	IEEE 802.11n, IEEE 802.11g, IEEE 802.11b
<b>Antenna</b>	2*5dBi Fixed Omni Directional Antenna
<b>Dimensions ( W x D x H )</b>	7.6 x 5.1 x 1.3 in.(192 x 130 x 33 mm)

### WIRELESS FEATURES

<b>Frequency</b>	2.4-2.4835GHz
<b>Signal Rate</b>	11n: Up to 300Mbps(dynamic) 11g: Up to 54Mbps(dynamic) 11b: Up to 11Mbps(dynamic)
<b>EIRP</b>	<20dBm(EIRP)
<b>Reception Sensitivity</b>	270M: -68dBm@10% PER 130M: -68dBm@10% PER 108M: -68dBm@10% PER 54M: -68dBm@10% PER 11M: -85dBm@8% PER 6M: -88dBm@10% PER 1M: -90dBm@8% PER
<b>Wireless Functions</b>	Enable/Disable Wireless Radio, WDS Bridge, WMM, Wireless Statistics
<b>Wireless</b>	64/128/152-bit WEP / WPA / WPA2,WPA-PSK / WPA2-PSK

### SOFTWARE FEATURES

<b>WAN Type</b>	Dynamic IP/Static IP/PPPoE/ PPTP/L2TP/BigPond
<b>DHCP</b>	Server, Client, DHCP Client List, Address Reservation
<b>Quality of Service</b>	WMM, Bandwidth Control
<b>Port Forwarding</b>	Virtual Server,Port Triggering, UPnP, DMZ
<b>Dynamic DNS</b>	DynDns, Comexe, NO-IP

**SOFTWARE FEATURES**

<b>VPN Pass-Through</b>	PPTP, L2TP, IPSec (ESP Head)
<b>Access Control</b>	Parental Control, Local Management Control, Host List, Access Schedule, Rule Management
<b>Firewall Security</b>	DoS, SPI Firewall IP Address Filter/MAC Address Filter/Domain Filter IP and MAC Address Binding
<b>Management</b>	Access Control Local Management Remote Management

**OTHERS**

<b>Certification</b>	CE, FCC, RoHS
<b>Package Contents</b>	Wireless N Router TL-WR841N Power supply unit Resource CD Quick Installation Guide
<b>System Requirements</b>	Microsoft® Windows® 98SE, NT, 2000, XP, Vista™ or Windows 7, MAC® OS, NetWare®, UNIX® or Linux.
<b>Environment</b>	Operating Temperature: 0~40°C (32~104°F) Storage Temperature: -40~70°C (-40~158°F) Operating Humidity: 10%~90% non-condensing Storage Humidity: 5%~90% non-condensing