



Firma: G Store & Repair doo
Adresa: Bul.Mihajla Pupina 10z/3
Telefon: 011 785 66 66
Fax:
PIB: 112029009
E-mail: office@gstore.rs

GMB-X96 AIR 4/32GB DDR3 smart TV box S905X3,
Mali G31 4K KODI Android 9.0 BT 2.4+5.8G,

Šifra: 105883

Kategorija proizvoda: TV box i resiveri

Proizvođač: GEMBIRD

Cena: 7.498 rsd.



CPU Amlogic S905X3 64-bit quad core ARM® Cortex™ A55 CPU

GPU G31™ MP2 GPU processor

Memory LPDDR3: 4GB

Flash eMMC:32GB

WiFi IEEE 802.11 a/b/g/n/ac ; 2.4G / 5G

Bluetooth BT ; Support Voice Remote

Mouldle Plastic : Black Color

1*HDMI: HDMI 2.1 ,Support HDMI CEC, Dynamic HDR and and 8Kx4K@24 max resolution output

1*AV OUT: 480i/576i standard definition output

3*USB: 1*USB 3.0; 2*USB 2.0

1*IR Reciver: Remote Reciver Connect

1*RJ45: Ethernet Interface;Support 10/100M

1*TF CARD: Support 4GB/8GB/16GB/32GB/64GB

Power DC 5V/2A;

OS Android 9.0

VIDEO:

Amlogic Video Engine (AVE) with dedicated hardware decoders and encoders

Support multi-video decoder up to 4x1080P@60fps

Supports multiple "secured" video decoding sessions and simultaneous decoding and encoding
Video/Picture Decoding

- VP9 Profile-2 up to 8Kx4K@24 fps

- H.265 HEVC MP-10@L5.1 up to 8Kx4K@24 fps

- AVS2-P2 Profile up to 8Kx4K@24 fps

- H.264 AVC HP@L5.1 up to 4Kx2K@30fps

- MPEG-4 ASP@L5 up to 1080P@60fps (ISO-14496)

- WMV/VC-1 SP/MP/AP up to 1080P@60fps

- AVS-P16(AVS+) /AVS-P2 JiZhun Profile up to 1080P@60fps

- MPEG-2 MP/HL up to 1080P@60fps (ISO-13818)

- MPEG-1 MP/HL up to 1080P@60fps (ISO-11172)

- RealVideo 8/9/10 up to 1080P@60fps

- Multiple language and multiple format sub-title video support

- MJPEG and JPEG unlimited pixel resolution decoding (ISO/IEC-10918)

- Supports JPEG thumbnail, scaling, rotation and transition effects

- Supports *.mkv,*.wmv,*.mpg, *.mpeg, *.dat, *.avi, *.mov, *.iso, *.mp4, *.rm and *.jpg file formats

AUDIO:

Supports MP3, AAC, WMA, RM, FLAC, Ogg and programmable with 7.1/5.1 down-mixing

Low-power VAD

Built-in serial digital audio SPDIF/IEC958 input/output and PCM input/output

3 built-in TDM/PCM/I2S ports with TDM/PCM mode up to 384kHz x 32bits x 16ch or 96kHz x 32bits x 32ch
and I2S mode up to