



Firma: G Store & Repair doo
Adresa: Bul.Mihajla Pupina 10z/3
Telefon: 011 785 66 66
Fax:
PIB: 112029009
E-mail: office@gstore.rs

GMB-T2-404 **DVB-T2 SET TOP BOX

USB/HDMI/Scart/RF-out, PVR, Full HD, H264, hdmi-kabl, modulator 1409

Šifra: 10968

Kategorija proizvoda: TV box i resiveri

Proizvođač: GEMBIRD

SRB	EM	Kopierjenim/Specifications
Maksimalna potrošnja	Maximum power consumption	<10w
Standby potrošnja	Standby power	<1w
Čipset	Chipset	Sunplus 1509C
Opseg frekvencije	Frequency Range	VHF 174~230MHz, UHF 470~862MHz
Kompatibilno sa video formatom	Compatible with video formats	480i/480p/567i/567p/720i/720p/1080p/1080i
Podrška	Supports	MPEG-1, MPEG-2, MPEG-4 and H.264 decoder
Video izlaz	Output port	HDMI,Scart,RF
Format dekodera	Decoder format	MPEG-4,WMA,AC3,AAC MKV,AVI
Audio izlaz	Audio output	Coaxial,Scart

Compatible with DVB-1 and DVB-T2



Cena: 2.169 rsd.

Features :

- 1.DVB-T2/DVB-1 compatible, supports MPEG4
2. Compatible with 480i/480P/576i/576p/720p/1,080i/1080P video formats
3. Sunplus 1509c chipset solution
4. Fully compliant with DVB-T1, DVB-T2 standard
5. Supports HDMI 1.4 (1080P)
6. Auto and manually scan all available TV and radio channels,Parental guidance locking
7. Auto/manual program search, multi-language supported
8. Supports MPEG-1, MPEG-2, MPEG-4 and H.264 decoder (up to 1,920 x 1,080 pixels)
9. Advanced audio processor supporting Dolby Digital
10. USB2.0 host support upgrade, PVR, time shifting and media play with U-Flash or HDD
11. Supports HDMI output, scart output, coaxial, RF in and output
- 12.Powerful and highly effective 7days EPG function

Tuner :

- *Input Frequency: VHF 174~230 MHZ, UHF 470~ 862 MHZ
- *RF input level: -78~20 dBm
- *RF Bandwidth: 7MHZ and 8MHZ
- *Signal input: IEC-type female
- *QPSK, 16QAM,64QAM, 256QAM
- *FEC: 1/2, 2/3, 3/4, 4/5, 5/6

Multimedia format :

- *Decoder format: MPEG 4 AVC/H.264 HP@L4MPEG2 MP@MP.HL
- *Output format:480i/480p/567i/567p/720i/720p/1080p/1080i
- *Output port: HDMI,AV/Scart(optional)
- *Decoder format: MPEG-1(layer 1&2&3),WMA.AC3,AAC
- *Audio output: Coaxial, L/R(AV or Scart)

Power :

- *Maximum power consumption: 10w *Standby power: 1w

Hardware Interface :

- *Indicators: Power, signal lock
- *IR Receiver: 38KHZ
- *LED Display *HDMI 1.4
- *Loop through output: IEC- type, connector,single tuner
- *Coaxial output *USB2.0
- *RF in & out *Scart Output

Packing :