



Firma: G Store & Repair doo
Adresa: Bul.Mihajla Pupina 10z/3
Telefon: 011 785 66 66
Fax:
PIB: 112029009
E-mail: office@gstore.rs

Tenda O9 outdoor long range Point to Point CPE 5GHz 11AC 867Mbps, 1xGbit, 23dBi, 25km

Šifra: 11138

Kategorija proizvoda: Ruteri

Proizvođač: TENDA



Cena: 10.085 rsd.

O9 5GHz 11ac 23dBi gigabit outdoor CPE is designed to PtP and PtMP solutions for private ISP wireless connectivity, CCTV surveillance and data transmission. It features with 23dBi directional dual polarization antenna to provide an efficient way to pick up and maintain a stable long-distance connectivity up to 25km. Adopt of auto-bridging technology, two CPE can connect to each other automatically to make it easy to setup.

Main Features

- 5GHz 11ac 867Mbps
- One Gigabit ethernet port
- 23dbi dual polarization antenna
- IP65 weatherproof enclosure
- 6000V Lightning Protection
- AP, Station, WISP operating mode supported
- Up to 60 meters of flexible deployment with included PoE adapter

O9 5GHz 11ac 23dBi gigabit outdoor CPE is designed to PtP and PtMP solutions for private ISP wireless connectivity, CCTV surveillance and data transmission. It features with 23dBi directional dual polarization antenna to provide an efficient way to pick up and maintain a stable long-distance connectivity up to 25km. Adopt of auto-bridging technology, two CPE can connect to each other automatically to make it easy to setup.

Dimension 391.5*280*223mm

Deployment Pole Mount

Application Scenarios PtP and PtMP wireless connection for Private ISP access or CCTV Surveillance

Frequency Range 5GHz

Compliant Standards IEEE 802.11a/n/ac

Private TDMA Protocol TD-MAX

Maximum Wireless Rate 867Mbps

Interface 1*10/100/1000Mbps Ethernet Port

Antenna gain 23dBi

Antenna Beamwidth Horizontal: 10° Vertical: 10°

Reset Button 1

Power Consumption 7.5W

Waterproof Level IP65

LED indicator PoE/LAN, LED1, LED2, LED3

Power Method 24V 0.5A Passive PoE

Lightning Protection 6000V

Passive PoE Passive power over ethernet via PoE/LAN (+4,5pins
-7,8pins)

Voltage range: 21-25V DC

Reception Sensitivity 11a 6Mbps -96dBm±1.5dBm

11n MCS7 HT20 -72dBm±1.5dBm