



Firma: G Store & Repair doo  
Adresa: Bul.Mihajla Pupina 10z/3  
Telefon: 011 785 66 66  
Fax:  
PIB: 112029009  
E-mail: [office@gstore.rs](mailto:office@gstore.rs)

---





## Tenda P200 KIT, 10/100Mbps, Powerline Network Adapter HomePlug, pakovanje 2Kom

Šifra: 11233

Kategorija proizvoda: PoE Adapteri

Proizvođač: TENDA



**Cena: 5.748 rsd.**

To build a network at home or office with minimum effort and cost, the Tenda 200Mbps Powerline Adapter P200 is your choice. In many cases, Ethernet is just not available in places where network connectivity is needed. However, almost every room at home or office has power circuitry, which can be used to extend network connections from your broadband router. Simply plug one P200 that links to a broadband modem/router into the power outlet in one room, and plug another P200 linking to a PC or any Ethernet device in the other, you can then easily and instantly create a powerline network of up to 200Mbps, 2X of a traditional switch or router, with the driving capability of up to 300 meters, 3X of Ethernet cable. Plus the QoS feature prioritizes your bandwidth intensive applications for lag-free experience.

To build a network at home or office with minimum effort and cost, the Tenda 200Mbps Powerline Adapter P200 is your choice. In many cases, Ethernet is just not available in places where network connectivity is needed. However, almost every room at home or office has power circuitry, which can be used to extend network connections from your broadband router. Simply plug one P200 that links to a broadband modem/router into the power outlet in one room, and plug another P200 linking to a PC or any Ethernet device in the other, you can then easily and instantly create a powerline network of up to 200Mbps, 2X of a traditional switch or router, with the driving capability of up to 300 meters, 3X of Ethernet cable. Plus the QoS feature prioritizes your bandwidth intensive applications for lag-free experience.

Speed Poweline 200Mbps

Standard&Protocol HomePlugAV

IEEE 802.3,IEEE 802./3u

Interface 1\*10/100M(Ethernet Interface)

Modulation Technology OFDM,CSMA/CA

Button1\*Pair/Reset

LED indicator1\*Power

1\*Powerline

1\*Ethernet

Power Consumption Maximum: 2.8W (220V/50Hz)

Minimum: 0.43W (220V/50Hz)

Power Input AC 100~240V 50/60Hz 0.1A

Frequency Powerline:2-30MHz

Dimension 53mm\*53mm\*27mm

Certification CE,FCC,RoHs

Plug Type EU,UK,US

Package Content AV200 Powerline Adapter

Quick Installation Guide

Ethernet Cable

Environment Operating Temperature: 0°C ~ 40°C(32°F ~ 104°F)

Storage Temperature: -40°F ~ 158°F (-40°C ~ 70°C )

Operating Humidity:10% ~ 90% RH non-condensing

Storage Humidity:5% ~ 90%RH non-condensing.

Related Products PW201A