



Firma: G Store & Repair doo
Adresa: Bul.Mihajla Pupina 10z/3
Telefon: 011 785 66 66
Fax:
PIB: 112029009
E-mail: office@gstore.rs

IP-COM G1008 LAN 8-Port 10/100/1000M Switch Ethernet ports (Auto MDI/MDIX) (alt=TEG1008D)



Šifra: 11234

Kategorija proizvoda: Switch uređaji

Proizvođač: IP-COM

Cena: 3.951 rsd.

8-Port Gigabit Unmanaged Desktop Switch

8 * 10/100 / 1000Mbps adaptive RJ45 port

Support loop guard, effectively lifting loop and the second line of the loop itself

Support port lightning, lightning protection rating of the whole port 4KV

9K jumbo frame support, improve network transmission efficiency

Support for desktop / wall installation, plug and play

G1008 is designed by IP-COM which is specifically for video surveillance of a story full Gigabit unmanaged switch products. Provides eight 10/100 / 1000M auto-sensing ports, all ports support wire-speed forwarding rate up to 1000Mbps, lightning rating per port up to 4KV, to ensure the stability and reliability. G1008 high performance, high reliability, as you build more speed more stable gigabit-level monitoring network.

Port Lightning

Built-in professional lightning protection circuit, the whole port lightning rating of 4KV, ensure the stable operation of the network thunderstorm days

Loop protection

Support loop guard, effectively lifting loop and the second line of the loop itself, to ensure the efficient operation of the network

9K jumbo frames

9K jumbo frame support and accelerate large file transfers and improve network transmission efficiency

Good Radiating

Iron desktop chassis design, large volume of space, bringing a strong heat, improve stability

Switch 8 Gigabit port Unmanaged Switches

Standard IEEE802.3 10Base-T

IEEE802.3u 100 Base-TX

IEEE802.3ab

Port and module 8 gigabit port(Auto MDI/MDIX)

Backplane bandwidth 16Gbps

Packet forwarding rate 11.9Mpps

MAC address entries 4k

Dimension 186.7mmX106.7mmX33.3mm(L*W*H)

Weight 2kg

Power supply DC 9V 600mA

Operating temperature & humidity 0? ~45?|10%~90%(noncondensing)

storage temperature & humidity -40?-70?|5%~90% RH (noncondensing)

Port feature Support "video surveillance" for monitoring the environment

Support loopback or second line anti-ring loop port

Support 4KV port Lightning proof

Tenda