

Firma: G Store & Repair doo Adresa: Bul.Mihajla Pupina 10z/3

Telefon: 011 785 66 66

Fax:

PIB: 112029009

E-mail: office@gstore.rs

ThendaoMWI5So(3ypack)nAG1200 dual band 2.4+5GHz d

Tenda MW5S (3 pack) AC1200 dual band 2.4+5GHz distribution mesh WiFi system 330m2

Šifra: 11239

Kategorija prozivoda: Ruteri

Proizvođač: TENDA

Cena: 15.773,00 rsd.

The Tenda nova MW5s is a whole home mesh WiFi system designed for larger households with 100 Mbps or greater broadband services. Powered by Tenda's mesh technology, each node automatically connects to the other, creating a distributed network throughout your entire home. A 3-pack of MW5s covers up to 3500 square feet. The primary node features gigabit ports, getting the most out of your 100 Mbps or greater broadband service and ensuring smooth playback of 4K videos. And the wall-plug secondary node connects to your existing Mesh network automatically with pre-paired configuration, making setup a breeze.

Works well with high speed broadband

With 2 gigabit ports included, the MW5s gets the most out of your high speed broadband services coming into your home.

Covers up to 3500 square feet

Powered by Tenda's proprietary mesh technology, each node automatically connects to the other, creating a distributed network throughout your entire home. A 3-pack of nova MW5s covers up to 3500 square feet. Go big and easily expand your WiFi network in the future simply by adding nodes.

Two external power amplifiers used both on 2.4 GHz and 5 GHz bands of the primary node to enhance the signal strength and receiving capability, helping the nova MW5s outperform ordinary routers.

Built-in dual band antennas for excellent wall penetration capability

With features that optimize both the 2.4 GHz and 5 GHz bands, the nova MW5s system automatically adjusts the data rates when it works behind multiple walls.

Beamforming technology concentrates the signal for better wall penetration

Powered by Beamforming technology, the nova MW5s projects a stronger WiFi signal in a direction where your devices are located. Instead of just broadcasting signals to a wide area, Tenda's Beamforming concentrates the signal and aims it directly at the target.

Automatic networking makes setup a breeze

All nodes are delivered pre-paired right out of the box, making the system easy to setup and an ideal choice for whole home WiFi coverage

Supports up to 60 devices

Combining the 1 GHz main chip with MU-MIMO technology, the nova MW5s communicates simultaneously with multiple devices, ensuring a lag-free internet connection when you enable the Capacity-oriented Mode using the App.

Standard&Protocol IEEE 802.3, IEEE 802.3u PortMesh5: 2 x 10/100/1000Mbps Ethernet ports

1 WAN/LAN port

1 LAN port

Mesh3f: 2 x 10/100Mbps Ethernet ports

1 WAN/LAN port

1 LAN port

Antenna Mesh5: 2 x 3 dBi built-in omni-directional antennas

Mesh3f: 2 x 3 dBi built-in omni-directional antennas

Button Mesh5: 1 x Reset button

Mesh3f: 1 x Reset button

Power Mesh5

Input: 100 - 240 V, 50/60 Hz, 0.6 A

Output: DC 12 V == 1 A

Mesh3f

Input: 100 - 240V, 50/60 Hz, 0.3 A

Output: 9 V 1A

Indicator Mesh5: 1 System/Signal

Mesh3f: 1 System/Signal

Dimension Mesh5: 91 mm x 91 mm x 93 mm (3.58 in. x 3.58 in. x 3.66 in.)

Mesh3f: 91 mm x 91 mm x 93 mm (3.58 in. x 3.58 in. x 3.66 in.)

Wireless Standards5 GHz: IEEE 802.11ac/a/n

2.4 GHz: IEEE 802.11b/g/n Data Rate5GHz: 867 Mbps

2.4GHz: 300 Mbps

Frequency Simultaneous dual band 2.4 GHz & 5 GHz

Basic Features SSID Broadcast

Beamforming MU-MIMO

Wireless SecurityWPA2-PSK (default)

Wireless roamingCompliant with IEEE 802.11k/v/r

Internet Connection TypePPPoE, Dynamic IP, Static IP, Bridge Mode

DHCP ServerDHCP Server

DHCP Client List

Virtual ServerPort Forwarding

UPnP

FirewallUDP flood attack defence

TCP flood attack defence

ICMP flood attack defence

DNSManually setting up DNS server

VPNIPsec pass through

PPTP pass through

L2TP pass through

OtherParental Control

Guest Network

Firmware upgrade online

Resetting to factory settings

Setup Requirements A mobile device running Android 4.0+ or iOS 8+

TemperatureOperating Temperature: 0 °C - 40 °C

Storage Temperature: -40 °C - 70 °C

HumidityOperating Humidity: (10% - 90%) RH non-condensing

Storage Humidity: (5% - 90%) RH non-condensing

CertificationFCC, CE, RoHS, EAC, IC

Package Content(3-pack)

Mesh5 x 1, Mesh3f x 2

12V/1A Power adapter x 1

9V/1A power adapter x 2

Quick installation guide x 1

Gigabit Ethernet cable x 1