

Firma: G Store & Repair doo Adresa: Bul.Mihajla Pupina 10z/3

Telefon: 011 785 66 66

Fax:

PIB: 112029009

E-mail: office@gstore.rs

Tenda RX3 AX1800 wireless dual band ruter 2.4+5GHz, 1W/3L 10/1000, 1.5Ghz cpu, 4x6dBi ,12v/1

Šifra: 11346

Kategorija prozivoda: Ruteri

Proizvođač: TENDA

Cena: 8.182,00 rsd.

Faster, More Stable and More Connection AX1800 Dual Band Gigabit Wi-Fi 6 Router

Wi-Fi 6 for Ultra-Fast Transmission Speed

RX3 adopts MU-MIMO + OFDMA to significantly improve network performance and efficiency, enabling it to support more client devices at the same time, wipe out latency, enhance multiplayer online games, and enjoy 4K videos more smoothly.

Built-in Signal Enhancement Module

It adopts 5GHz dedicated powerful WLAN full-featured front-end module, equipped with integrated signal amplifier. The concentrated signal makes sure stronger and more stable Multi-story home Wi-Fi coverage. You can enjoy best signal in any corners.

1.5GHz Quad Core Processor

Provides Faster and More Stable Wi-Fi

With the 1.5GHz high-performance quad core processor, the network load capacity is comprehensively improved. Instant fast response making the operation more stable.

RX3

BSS Coloring Reduces Interference and Improves Efficiency

Supporting BSS coloring technology,RX3 effectively alleviates co-frequency interference, improves spectrum utilization and communication efficiency.

TWT Extends Battery Life of Connected Devices

TWT (Target Wake-up Time technology) can effectively reduce the power consumption of terminal equipment and greatly extend its battery life.

Enjoy Safer Surfing with The Next-Gen Security Protocol WPA3

The RX3 carries a new generation of WiFi security standard WPA3, which increases the difficulty of algorithmic and network password cracking, can prevent forced- attacks, violent cracking, and protect user privacy in open Wi-Fi networks.

Remote Control Through The Tenda APP

Wi-Fi status can be controlled remotely through the Tenda APP, even while travelling, which facilitates the real-time monitoring of routers.

Live The Present Greet The Future

The RX3 is designed to be compatible with Smartphones & devices that support Wi-Fi 6 standard in use. Enjoy the latest generation Wi-Fi standard with the RX3 from Tenda.

Hardware Standard&Protocol IEEE802.3, IEEE802.3u,IEEE802.3ab



Interfaces 1*10/100/1000Mbps WAN port 3*10/100/1000Mbps LAN ports Antenna 4*6dBi external antennas Button 1* WPS,1*Reset button Power Input:AC 100-240V~50/60Hz 0.4 Output:DC 12V 1A Dimension 9.35*6.03*1.77 in (237.6*153.1*45mm) LED Indicator SYS*1 Wireless Wireless Standard IEEE 802.11ac/a/n/ax 5GHz IEEE 802.11b/g/n/ax 2.4GHz Data Rate 5GHz: Up to 1201Mbps 2.4GHz: Up to 574Mbps Frequency Simultaneous dual band 2.4 & 5GHz Transmission Power CE: **Basic Features** SSID Broadcast: Enable/Disable Transmission Power: high, medium, low Beamforming **MU-MIMO** Wireless Security WPA-PSK, WPA2-PSK, WPA/WPA2-PSK WPA3-SAE/WPA2-PSK Wireless Security: Enable/Disable WPS(WiFi Protected Set-up) fast encryption Software Internet Connection Type PPPoE, Dynamic IP, Static IP PPPoE(Russia), PPTP(Russia), L2TP(Russia), Unifi, Maxis, Maxis-special, Manual Operating Mode Wireless Router Mode Universal Repeater Mode WISP Mode **DHCP Server DHCP Server DHCP Client List DHCP Reservation** Virtual Server Port Forwarding DMZ Host **UPnP** Security Client Filter Parental Control(support black list and white list) Remote Web Management **Firewall** Forbid UDP flood attack Forbid TCP flood attack Forbid ICMP attack Forbid WAN PING from internet **DDNS**

no-ip,Oray, 88ip,DynDNS VPN

PPTP server

PPTP client

L2TP client

Special Features

Smart Traffic Prioritisation

PPPoE Username/password Clone

Smart WiFi Schedule

Smart LED on/off

Tenda Cloud

Tenda App

Alexa

Others

Bandwidth Control

Guest Network

IPTV

VLAN

MAC Clone

Static Routing

System Log

Backup & Restore configurations

Firmware upgrade online

Firmware upgradeable via browser

Supports IPv6

Others

Temperature

Operating Temperature: $0? \sim 40$? Storage Temperature: -40? ~ 70 ?.

Humidity

Operating Humidity: $10\% \sim 90\%$ RH non-condensing Storage Humidity: $5\% \sim 90\%$ RH non-condensing.

Default Settings

Default Access: tendawifi.com

Certification CE/FCC/RoHS EIRP Power (Max)

2.400-2.4835GHz:19.86dBm (EIRP)

5.150-5.250GHz:22.96dBm (EIRP)

Package Contents Wireles Router*1

Power Adapter *1

Install Guide*1

Ethernet Cable*1