



Firma: G Store & Repair doo
Adresa: Bul.Mihajla Pupina 10z/3
Telefon: 011 785 66 66
Fax:
PIB: 112029009
E-mail: office@gstore.rs

Tenda O4 outdoor long range Point to Point CPE 5GHz 300Mbps, 14dBi, 5km

Šifra: 11498

Kategorija proizvoda: Ruteri

Proizvođač: TENDA



Cena: 7.595 rsd.

5km Point to Point Outdoor CPE

O4 5GHz Long Range Outdoor CPE is designed to WISP CPE solutions and long distance wireless network solutions for video surveillance and data transmission. It features with 14dBi directional antenna to provide an efficient way to pick up and maintain a stable signal for a wireless network. Adopt of auto-bridging technology, two CPE can connect to each other automatically to make it easy to setup.

O4 adopts of independent power amplifier and 14dBi directional antenna to provide an efficient way to pick up and maintain a stable signal for a wireless network up to 5km.

Super channel-Extended Frequency

O4 adopt of Qualcomm AR9344 chipset and special software mechanism optimization for radio driven architecture to offer extended frequency support. This feature is designed to help users get out of the congested, unlicensed 5GHz band and into clean spectrum.

TD-MAX-Tenda TDMA proprietary protocol

TD-MAX is Tenda TDMA (Time Division Multiple Access) proprietary protocol to improve performance and capacity for wireless WISP outdoor application scenarios.

In outdoor environment, the CPE use highly directional antennas to connect to the Basestation from distances that can span several kilometers. the CPE can't sense each other, they become "hidden nodes" and cannot coordinate access to the wireless channel. Thus the Basestation experiences frequent collisions from stations transmitting simultaneously. As the network scales, these collisions build up exponentially, increasing latency and lowering throughput. With TD-MAX, it coordinate all the data transmission and allocates time to active clients to provide greater noise immunity performance when compared to the conventional 802.11 CSMA/CA (Carrier Sense Multiple Access / Collision Avoidance) protocol.

10/20/30/40MHz Channel Bandwidth for better throughput

O4 apply special optimization in software for register parameter to deliver 10/20/30/40MHz channel bandwidth option. It provides extra 10MHz and 30MHz channel bandwidth option to consumize according to application scenarios.

When you choose 30MHz channel bandwidth option, it can increase throughput for noisy environments.

When you choose 10MHz channel bandwidth option, it can increase the number of available, non-overlapping channels, so networks can scale better.

Channel shift to avoid interference

O4 provide Channel Shift feature to offset the central frequency 5MHz upper. It can avoid interference from nearby AP and deliver higher throughput.

Dimension 270*94.86*67.5mm

Deployment Pole Mount/Wall Mount

Application Scenarios: PtP and PtMP wireless connection for Privated ISP access or CCTV Surveillance

Frequency Range 5GHz