



Firma: G Store & Repair doo
Adresa: Bul.Mihajla Pupina 10z/3
Telefon: 011 785 66 66
Fax:
PIB: 112029009
E-mail: office@gstore.rs

Tenda O3 outdoor long range Point to Point CPE 2.4GHz 150Mbps, 12dBi, 5km

Šifra: 11501

Kategorija proizvoda: Ruteri

Proizvođač: TENDA



Cena: 7.615 rsd.

O3 2.4GHz Outdoor CPE is designed to WISP CPE solutions and long distance wireless network solutions for video surveillance and data transmission. It features with 12dBi directional antenna to provide an efficient way to pick up and maintain a stable signal for a wireless network. Adopt of auto-bridging technology,two CPE can connect to each other automatically to make it easy to setup

- 2.4GHz 11n 150Mbps
- 12dbi directional antenna
- IP64 waterproof enclosure
- 6000V Lightning Protection
- AP,Station,WISP operating mode supported
- Up to 60 meters of flexible deployment with included PoE Injector

5km+ transmission Range

O3 adopts of independent power amplifier and 12dBi directional antenna to provide an efficient way to pick up and maintain a stable signal for a wireless network up to 5km.

Auto-bridge For Two Device

O3 adopts of auto-bridge technology,two cpe can connect to each other when you power on them face to face. It is very easy to setup for CCTV surveillance and data.

Smart Signal Indicator LED

3 signal LED Lights represent the currently signal strength that O3 receives from peer device.It is helpful to find the right location to deploy the device and achieve a better performance.

Professional Outdoor Design

Equipped with IP64 waterproof enclouse and high quality hardware design, O3 can work in various weather conditions, such as sunshine, rainfall or extremely low/high temperature environment

Long-Distance Wireless Connection

One work as AP mode and another work as Station mode to create a long distance wrieless connecton for video surveillance and data transmission.

WISP(Client+Router) Mode

Wirelessly connect to WISP station/hotspot to share Internet to local wireless and wired network

Dimension 270*94.86*67.5mm

Deployment Pole Mount/Wall Mount

Application Scenarios PtP and PtMP wireless connection for Privated ISP access or CCTV Surveillance

Frequency Range: 2.4GHz

Compliant Standards: IEEE 802.11b/g/n

Maximum Wireless Rate: 150Mbps