



Firma: G Store & Repair doo
Adresa: Bul.Mihajla Pupina 10z/3
Telefon: 011 785 66 66
Fax:
PIB: 112029009
E-mail: office@gstore.rs

MB s1851 AsRock Z890 Lightning WiFi

Šifra: 143606

Kategorija proizvoda: Matične ploče

Proizvođač: ASRock

Cena: 31.627 rsd.



- Thunderbolt™ 4 Type-C Ports (40 Gb/s)

Rock-Solid Durability

- Server-Grade Low-Loss PCB
- 18+1+1+1+1 Power Phase, 80A SPS for VCore+GT+SA with Enlarged Heatsink Armor
- Memory OC Shield
- Flexible Integrated I/O Shield
- 20K Long-lasting Black Caps (high quality and conductive polymer capacitors)

Ultrafast Gaming

- Killer 2.5G LAN, 802.11be Wi-Fi 7 Module
- ASRock Lightning Gaming Ports

EZ Update

- BIOS Flashback Button
- ASRock Auto Driver Installer

EZ Troubleshooter

- [ASRock Post Status Checker](#)

Chipset

- Intel® Z890

BIOS

- 256Mb AMI UEFI Legal BIOS with GUI support

Audio

- 7.1 CH HD Audio with Content Protection (Realtek ALC1220 Audio Codec)

- Impedance Sensing on Rear Out port

Wireless LAN

- 802.11be Wi-Fi 7 Module

- Supports IEEE 802.11a/b/g/n/ac/ax/axe/be

- Supports 2.4GHz/5GHz/6GHz frequency band*

- Supports 320MHz channel bandwidth with 6GHz frequency band*

- 1 antenna to support 2 (Transmit) x 2 (Receive) diversity technology

CPU

- Supports Intel® Core™ Ultra Processors (Series 2) (LGA1851RL-ILM)

- Supports Intel® Hybrid Technology

- Supports Intel® Turbo Boost Max 3.0 Technology

- Supports Intel® Thermal Velocity Boost (TVB)

- Supports Intel® Adaptive Boost Technology (ABT)

- Integrated NPU for dedicated AI acceleration

Memory

- Dual Channel DDR5 Memory Technology

- 4 x DDR5 DIMM Slots

- Supports DDR5 non-ECC, un-buffered memory up to 9466MHz+(OC)*

- Supports Clocked Unbuffered DIMM (CUDIMM)

- Max. capacity of system memory: 256GB

- Supports Intel® Extreme Memory Profile (XMP) 3.0x

* 1DPC 1R Up to 9466+ MHz (OC), 5600 MHz Natively.

1DPC 2R Up to 6800+ MHz (OC), 5600 MHz Natively.

2DPC 1R Up to 6800+ MHz (OC), 4800 MHz Natively.

2DPC 2R Up to 5800+ MHz (OC), 4400 MHz Natively.

Graphics

- Intel® Xe LPG Graphics Architecture

- 1 x HDMI 2.1 TMDS/FRL 8G Compatible, supports HDR, HDCP 2.3 and max. resolution up to 4K 120Hz

- 2 x Intel® Thunderbolt™ 4, support HDCP 2.3 and max. resolution up to 8K 60Hz / 5K 120Hz*

* Intel® UHD Graphics Built-in Visuals and the VGA outputs can be supported only with processors which are GPU integrated.

Supports two 4K displays or one 8K display

Only the CPU's embedded graphics can be displayed through Thunderbolt™ ports.

If you want to display to a Thunderbolt™ monitor, please use CPU models with embedded graphics.

LAN

- 2.5 Gigabit LAN 10/100/1000/2500 Mb/s

- Killer E3100G

- Supports Killer LAN Software

Slots

CPU:

- 1 x PCIe 5.0 x16 Slot (PCIe1), supports x16 mode*

Chipset: