



Firma: G Store & Repair doo  
Adresa: Bul.Mihajla Pupina 10z/3  
Telefon: 011 785 66 66  
Fax:  
PIB: 112029009  
E-mail: [office@gstore.rs](mailto:office@gstore.rs)

---

## Svič 10100 16-port Cudy FS1016 metalno kućište

Šifra: 163031

Kategorija proizvoda: Switch uređaji

Proizvođač: CUDY

**Cena: 3.167 rsd.**



<b>Model Version</b>	FS1016 1.0
<b>10/100 Mbps RJ45 Ports</b>	16
<b>Shielded RJ45 Port</b>	True
<b>Extend Mode Ports</b>	#1~#14
<b>VLAN Mode Ports</b>	#1~#14
<b>LED</b>	Power, Link/ACT of each Ethernet Port
<b>Power Interfaces</b>	AC Inlet
<b>Physical Buttons</b>	VLAN/Default/Extend DIP Switch
<b>Copper Speed &amp; Distance</b>	Cat.3+: 100 m @ 10 Mbps Cat.5+: 100 m @ 100 Mbps Cat.5e+: 250 m @ 10 Mbps
<b>Copper Speed Note</b>	250 m transmission only on Extend Mode ports when activated
<b>MAC Address Table</b>	8192

<b>Max Switching Capacity</b>	3.2 Gbps
<b>Max Forwarding Rate</b>	2.38 Mpps
<b>Jumbo Frame</b>	2 KB
<b>Packet Buffer</b>	2 Mbit
<b>Power Saving</b>	Basic Power Saving: True
<b>Power Methods</b>	AC
<b>Power Input</b>	90-260V~ 50/60Hz
<b>Max Power Consumption</b>	2.0 W
<b>Idle Power Consumption</b>	0.8 W
<b>Switching Protocols</b>	802.3i, 802.3u, 802.3x Flow Control
<b>Grounding Methods</b>	Three-Prong Plug, Grounding Point
<b>EMS</b>	IEC/EN 61000-4-2 Level 3 ESD: Contact 6kV, Air 8kV IEC/EN 61000-4-5 Level 4 Surge: Power DM 2kV, CM 4kV; RJ45 CM 4kV
<b>Operating Temperature</b>	0~40 °C (32~104 °F)
<b>Storage Temperature</b>	-40~70 °C (-40~158 °F)
<b>Operating Humidity</b>	10~90% non-condensing