



Firma: G Store & Repair doo  
Adresa: Bul.Mihajla Pupina 10z/3  
Telefon: 011 785 66 66  
Fax:  
PIB: 112029009  
E-mail: [office@gstore.rs](mailto:office@gstore.rs)

---

Svič 101001000 24-port Cudy GS1024E  
Rackmount Light Managed

Šifra: 163051

Kategorija proizvoda: Switch uređaji

Proizvođač: CUDY



**Cena: 7.809 rsd.**

Model	GS1024E 1.0
Gigabit RJ45 portovi	24
Zaštićeni RJ45 portovi	Da
Extend Mode portovi	#1~#22
VLAN Mode portovi	#1~#22
LED indikatori	Power, Speed/Link/Act svakog porta
Priključci za napajanje	AC ulaz
Fizički tasteri	Managed/VLAN/Extend/Reset DIP Switch
Brzina prenosa i udaljenost	Cat. 3+: 100 m @ 10 Mbps Cat. 5+: 100 m @ 100 Mbps Cat. 5e+: 100 m @ 1 Gbps Cat. 5e+: 250 m @ 10 Mbps Cat. 6+: 150 m @ 1 Gbps
Napomena o udaljenosti	250 m prenos je moguć na Extend Mode portovima kada je Extend Mode aktiviran. U Managed modu, 250 m prenos je moguć pri brzini 10 Mbps podešenoj u softveru
MAC Address tabela	8192

Maksimalni kapacitet switchinga	48 Gbps
Maksimalna brzina prosleđivanja	35.712 Mpps
Jumbo Frame	15 KB
Packet buffer	4 Mbit
Basic Power Saving	Da
Način napajanja	AC
Ulaz napajanja	90-260V~, 50/60Hz
Maksimalna potrošnja	11 W
Potrošnja u praznom hodu	6.8 W
Podržani 802.3 protokoli	802.3x Flow Control, 802.3i 10BASE-T, 802.3u 100BASE-TX, 802.3ab 1000BASE-T, 802.3az Power Saving
Podržani 802.1 protokoli	802.1d STP, 802.1w RSTP, 802.1p LAN Layer 2 QoS/CoS, 802.1q VLAN Bridge, 802.1ab LLDP/LLDP-MED
Upravljanje portovima	Port On/Off, Port Negotiation Speed, Port Trunk (Static Aggregation), Port Mirror, Data Rate Limit, Jumbo Frame Settings, Storm Control, Traffic Monitor, MAC Address Management, EEE (802.3az)
Port Mirror sesije	4
Port Trunk grupe	4