



Firma: G Store & Repair doo  
Adresa: Bul.Mihajla Pupina 10z/3  
Telefon: 011 785 66 66  
Fax:  
PIB: 112029009  
E-mail: [office@gstore.rs](mailto:office@gstore.rs)

---

## MB s1200 GIGABYTE B560M DS3H V2

---

Šifra: 22190

Kategorija proizvoda: Matične ploče

Proizvođač: GIGABYTE

**Cena: 11.835 rsd.**



processors / Intel®  
Core™ i5 processors  
10th Generation Intel®  
Core™ i9 processors /  
Intel® Core™ i7  
processors / Intel®  
Core™ i5 processors /  
Intel® Core™ i3  
processors/ Intel®  
Pentium® processors /  
Intel® Celeron®  
processors\*

\* Limited to processors  
with 4 MB Intel® Smart  
Cache, Intel® Celeron®  
11th Generation Intel®  
Core™ i9/i7/i5

L3 cache varies with CPU  
processors:  
(Please refer to "CPU Support List" for more  
information.)  
Support for DDR4  
5333(O.C.) / DDR4

5133(O.C.) / DDR4  
5000(O.C.) / 4933(O.C.) /  
4800(O.C.) / 4700(O.C.) /  
4600(O.C.) / 4500(O.C.) /  
4400(O.C.) / 4300(O.C.) /  
4266(O.C.) / 4133(O.C.) /  
4000(O.C.) / 3866(O.C.) /  
3800(O.C.) / 3733(O.C.) /  
3666(O.C.) / 3600(O.C.) /  
3466(O.C.) / 3400(O.C.) /  
3333(O.C.) / 3300(O.C.) /  
3200 / 3000 / 2933 /  
2800 / 2666 / 2400 /  
2133 MHz

10th Generation Intel®  
Core™ i9/i7 processors:  
Support for DDR4  
2933/2666/2400/2133  
MHz memory modules

10th Generation Intel®  
Core™ i5/i3/Pentium®  
/Celeron® processors:  
Support for DDR4  
2666/2400/2133 MHz  
memory modules  
4 x DDR4 DIMM sockets  
supporting up to 128 GB  
(32 GB single DIMM  
capacity) of system  
memory

Dual channel memory  
architecture  
Support for ECC Un-  
buffered DIMM  
1Rx8/2Rx8 memory  
modules (operate in non-  
ECC mode)

Support for non-ECC Un-  
buffered DIMM

#### Chipset

Intel® B560 Express  
Chipset

#### Onboard Graphics

Integrated Graphics Processor-Intel® HD Graphics  
support:

1 x DVI-D port,  
supporting a maximum  
resolution of  
1920x1200@60 Hz  
\* The DVI-D port does  
not support D-Sub  
connection by adapter.

1 x DisplayPort,  
supporting a maximum  
resolution of  
4096x2304@60 Hz

\* Support for DisplayPort  
1.2 with HDCP 2.3  
supporting a maximum