



Firma: G Store & Repair doo  
Adresa: Bul.Mihajla Pupina 10z/3  
Telefon: 011 785 66 66  
Fax:  
PIB: 112029009  
E-mail: [office@gstore.rs](mailto:office@gstore.rs)

---

## MB ASUS s1200 ROG STRIX B560-A GAMING WIFI

---

Šifra: 22195

Kategorija proizvoda: Matične ploče

Proizvođač: ASUS

**Cena: 27.710 rsd.**



## CPU

Supports Intel® 14 nm CPU

Supports Intel® Turbo Boost Technology 2.0 and Intel® Turbo Boost Max Technology 3.0\*\*

\* Refer to [www.asus.com](http://www.asus.com) for CPU support list.

\*\* Intel® Turbo Boost Max Technology 3.0 support depends on the CPU types.

## Chipset

B560

## Memory

Dual Channel Memory Architecture

Supports Intel® Extreme Memory Profile (XMP)

OptiMem II

\* 10th Gen Intel® i7/i9 processors support 2933/2800/2666/2400/2133 natively, others will run at the maximum transfer rate of DDR4 2666MHz.

\* 11th Gen Intel® processors support 3200/2933/2800/2666/2400/2133 natively.

\* Refer to [www.asus.com](http://www.asus.com) for the Memory QVL (Qualified Vendors Lists), and memory frequency support depends on the CPU types.

## Graphics

\* Graphics specifications may vary between CPU types.

\*\*Only Intel® 11th processors, support DisplayPort 1.4 with max. resolution of 5120 x 2880 @60Hz, others would only support DisplayPort 1.4 with max. resolution of 4096 x 2304 @60Hz .Please refer to [www.intel.com](http://www.intel.com) for any update.

\*\*\* Only Intel® 11th processors support HDMI™ 2.0 with max. resolution of 4K@60Hz, others will only support HDMI™ 1.4 with max. resolution of 4K@30Hz. Please refer to [www.intel.com](http://www.intel.com) for any updates.

## Expansion Slots

### Intel® 11th &10th Gen Processors

1 x PCIe 4.0/3.0 x16 slot(s)

- Intel® 11th processors support PCIe 4.0 x16 mode

- Intel® 10th processors support PCIe 3.0 x16 mode

### Intel® B560 Chipset

1 x PCIe 3.0 x16 slot (supports x4 mode)\*

3 x PCIe 3.0 x1 slots

## Storage

Supports 2 x M.2 slots and 6 x SATA 6Gb/s ports

### Intel® 11th Gen Processors

M.2\_1 slot (Key M), type 2242/2260/2280/22110

- Only Intel® 11th processors support PCIe 4.0 x4 mode, this slot will be disabled for other CPUs.

### Intel® B560 Chipset

M.2\_2 slot (Key M), type 2242/2260/2280/22110 (supports PCIe 3.0 x4 & SATA modes)\*

6 x SATA 6Gb/s ports

\* When M.2\_2 runs at SATA mode, SATA6G\_1 will be disabled

\*\* To enable Intel® Optane™ Memory (Hybrid Storage device), it must be installed in PCH-attached slots with Intel® Rapid Storage Technology.

## USB

Rear USB:Total 9 ports

1 x USB 3.2 Gen 2x2 port(s) (1 x USB Type-C®)

1 x USB 3.2 Gen 2 port (1 x Type-A)

2 x USB 3.2 Gen 1 port (2 x Type-A)

5 x USB 2.0 port(s) (4 x Type-A, 1 x audio USB Type-C®)