



Firma: G Store & Repair doo
Adresa: Bul.Mihajla Pupina 10z/3
Telefon: 011 785 66 66
Fax:
PIB: 112029009
E-mail: office@gstore.rs

Šifra: 23450

Kategorija proizvoda: PoE Adapteri

Proizvođač: DAHUA

Cena: 19.167 rsd.

- > Intelligent PoE
- > PD Alive(PoE Watchdog) \
- > Long Distance PoE Transmission
- > Smooth Transmission
- > Wide Working Temperature: -10 to 55°C (14°F to 131°F)
- > Port Isolation

Performance

Layer: Layer 2

Managed: No

Switching Capacity: 7.2 Gbps

Packet Forwarding Rate: 5.3568 Mpps

Packet Buffer Memory: 4 Mbit

MAC Table Size: 8K

Standards Compliance: IEEE802.3, IEEE802.3u, IEEE802.3x, IEEE802.3ab, IEEE802.3z

Hardware Feature

Standard Power Supply: Yes

PoE: Yes

Ethernet Port: 16

Optical Port: 2

Ethernet Port Rate: 100 Mbps

Optical Port Rate: 1 Gbps

Number of Bussiness Card Slots:

Port 1-16: 16 × RJ45 10/100 Mbps

Port 17-18: 2 × RJ45 10/100/1000 Mbps (uplink)

Port 17-18: 2 × SFP 1000 Mbps (uplink) (combo)

Power Supply: 100V AC-240V AC

Operating Temperature: -10°C to 55°C (14°F to 131°F)

Operating Humidity: 10%-90%

Storage Humidity: 5%-95%

Power Consumption:

Idling: 5W

Full load: 135W

PoE Standard IEEE802.3af, IEEE802.3at, Hi-PoE:

PoE Budget: Port 1-2=60W, Port 3-16=30W, total=135W

PoE Pin Assignment: PoE/Hi-PoE: 1, 2, 4, 5 (V+), 3, 6, 7, 8 (V-)

Long Distance PoE Transmission: Yes

VLAN: Port Isolation

QoS: Yes

System Maintenance: PD Alive

ESD: