



Firma: G Store & Repair doo  
Adresa: Bul.Mihajla Pupina 10z/3  
Telefon: 011 785 66 66  
Fax:  
PIB: 112029009  
E-mail: [office@gstore.rs](mailto:office@gstore.rs)

---

## MB s1700 Gigabyte B660M GAMING X DDR4

---

Šifra: 23739

Kategorija proizvoda: Matične ploče

Proizvođač: GIGABYTE

**Cena: 16.996 rsd.**



for 12th Generation Intel  
® Core™, Pentium® Gold  
and Celeron®  
Processors\*  
Support for  
L3 cache varies with CPU  
DDR4 4400(O.C.) /  
\* Please refer to "CPU Support List" for more  
4300(O.C.) / 4266(O.C.) /  
information  
4133(O.C.) / 4000(O.C.) /  
3866(O.C.) / 3800(O.C.) /  
3733(O.C.) / 3666(O.C.) /  
3600(O.C.) / 3466(O.C.) /  
3400(O.C.) / 3333(O.C.) /  
3300(O.C.)

/3200/3000/2933/2666/2400/2133

MHz memory modules

4 x DDR DIMM sockets  
supporting up to 128 GB  
(32 GB single DIMM  
capacity) of system  
memory

Dual channel memory  
architecture

Support for ECC Un-  
buffered DIMM

1Rx8/2Rx8 memory  
modules (operate in non-  
ECC mode)

Support for non-ECC Un-  
buffered DIMM

1Rx8/2Rx8/1Rx16  
memory modules

Support for Extreme  
Memory Profile (XMP)  
memory modules

(Please refer "Memory Support List" for more  
information.)

## Audio

Realtek® Audio CODEC

High Definition Audio

2/4/5.1/7.1-channel

\* To configure 7.1-  
channel audio, you need  
to open the audio  
software and select  
Device advanced  
settings > Playback  
Device to change the  
default setting first.

Please visit GIGABYTE's  
website for details on  
configuring the audio  
software.

Support for S/PDIF Out

## Expansion Slots

1 x PCI Express x16 slot,

## Chipset

Intel® B660 Express

Chipset

## Onboard Graphics

Integrated Graphics Processor-Intel® HD Graphics  
support:

1 x HDMI port,  
supporting a maximum  
resolution of

4096x2160@60 Hz

\* Support for HDMI 2.1  
version and HDCP 2.3.

\*\* Support native HDMI  
2.1 TMDS compatible  
ports.

1 x DisplayPort,  
supporting a maximum  
resolution of

4096x2304@60 Hz

\* Support for DisplayPort  
1.2 version and HDCP 2.3

(Graphics specifications may vary depending on CPU  
support.)

## LAN

2.5GbE LAN chip (2.5

Gbps/1 Gbps/100 Mbps)