



Firma: G Store & Repair doo  
Adresa: Bul.Mihajla Pupina 10z/3  
Telefon: 011 785 66 66  
Fax:  
PIB: 112029009  
E-mail: [office@gstore.rs](mailto:office@gstore.rs)

---

MB AM4 Biostar B550MXE PRO  
4xDDR42xM.2HDMI2.0VGA

Šifra: 24492

Kategorija proizvoda: Matične ploče

Proizvođač: BIOSTAR



**Cena: 11.262 rsd.**

Tip procesora	Chipset AMD B550 CPU SUPPORT Socket AM4 support AMD Ryzen 3rd Gen (Matisse/ Renoir) and Ryzen 4th Gen (Vermeer/ Future) processors
Format ploče	Micro ATX Dimenzije: 24.4cm x 24.4cm
Memorija	4th Gen AMD Ryzen Processors (Vermeer CPUs/ Future APUs): Supports Dual Channel DDR4 4400+(OC)/ 4000(OC)/ 3800(OC)/ 3600(OC)/ 3200/ 2933/ 2667/ 2400/ 2133 3rd Gen AMD Ryzen Processors (Matisse CPUs): Supports Dual Channel DDR4 4400+(OC)/ 4000(OC)/ 3800(OC)/ 3600(OC)/ 3200/ 2933/ 2667/ 2400/ 2133 3rd Gen AMD Ryzen with Radeon Graphics Processors (Renoir APUs): Supports Dual Channel DDR4 4933+(OC)/ 4800(OC)/ 4600(OC)/ 4400(OC)/ 4000(OC)/ 3800(OC)/ 3600(OC)/ 3200/ 2933/ 2667/ 2400/ 2133 4 x DDR4 DIMM Memory Slot, Max. Supports up to 128 GB Memory Each DIMM supports non-ECC and ECC Un-buffered 8/ 16/ 32 GB DDR4 module
Slotovi za proširenje	1 x PCIe 4.0/ 3.0 x16 Slot (PCIEG4X16): Supports PCIe 3.0 x16/ 4.0 x16 mode with AMD Ryzen processors. Supports PCIe 3.0 x16 mode AMD Ryzen with Radeon Vega Graphics processors. 1 x PCIe 3.0 x16 Slot (PCIEG3X4) : Supports x4 mode 1 x PCIe 3.0 x1 Slot (PCIEG3X1) STORAGE -- Total supports 2 x M.2 socket and 4 x SATA III (6Gb/s) ports 4 x SATA III Connectors (6Gb/s) : Supports AHCI & RAID 0, 1, 10 1 x M.2 (M Key) Socket (M2_PCIEG4_64G_SATA): Supports M.2 Type 2242/ 2260/ 2280 SSD module Supports PCIe 4.0 x4 (64Gb/s)/ 3.0 x4 (32Gb/s) & SATA III (6.0Gb/s) SSD 1 x M.2 (M Key) Socket (M2_PCIEG3_32G_SATA): Supports M.2 Type 2242/ 2260/ 2280 SSD module Supports PCIe 3.0 x4 (32Gb/s) & SATA III (6.0Gb/s) SSD * M.2 (M Key) Socket (M2_PCIEG4_64G_SATA) : The bandwidth is depended on CPU. Supports PCIe 4.0 x4 (64Gb/s) speed, which depends only on Ryzen 3rd Gen Matisse and 4th Gen Vermeer CPUs.
Zvučna kartica	ALC897 7.1 Channels, High Definition Audio, Hi-Fi (Front)

## INTEGRATED VIDEO

By CPU model

Supports DX12

Supports HDCP

LAN Realtek RTL8111H

10/ 100/ 1000 Mb/s auto negotiation, Half / Full duplex capability

USB 6 x USB 3.2 (Gen1) ports (4 on rear I/Os and 2 via internal headers)

6 x USB 2.0 ports (2 on rear I/Os and 4 via internal headers)

Zadnji prikljucci:

2 x WIFI Antenna Ports

1 x PS/2 Keyboard / Mouse

1 x DVI-D Port

1 x VGA Port

1 x HDMI Port

1 x LAN port

4 x USB 3.2 (Gen1) Ports

2 x USB 2.0 Ports

3 x Audio Jack

Interni prikljucci:

4 x SATA III (6.0Gb/s) Connectors

1 x M.2 (E Key) Socket : Supports 2230 type Wi-Fi & Bluetooth module

2 x USB 2.0 Header (each header supports 2 USB 2.0 ports)

1 x USB 3.2 (Gen1) Header (each header supports 2 USB 3.2 (Gen1) ports)

1 x 8-Pin Power Connector

1 x 24-Pin Power Connector

1 x CPU Fan Connector

2 x System Fan Connectors

1 x Front Panel Header

1 x Front Audio Header

1 x Internal Stereo Speaker Header

1 x Clear CMOS Header

1 x S/PDIF out Connector

1 x COM Port Header

1 x TPM Header

1 x SYSTEM Status LED

\* M.2 (E key) Wi-Fi card is not provided

H/W MONITORING CPU / System Temperature Monitoring

CPU / System Fan Monitoring

Smart / Manual CPU Fan Control

System Voltage Monitoring

DIMENSION Micro ATX Form Factor

OS SUPPORT Supports Windows 10(64bit) / 11(64bit)

Ostalo