



Firma: G Store & Repair doo
Adresa: Bul.Mihajla Pupina 10z/3
Telefon: 011 785 66 66
Fax:
PIB: 112029009
E-mail: office@gstore.rs

MB AM4 GIGABYTE GA-A320M-S2H 1.2

Šifra: 2504

Kategorija proizvoda: Matične ploče

Proizvođač: GIGABYTE

Cena: 5.833 rsd.



AM4 Socket:

AMD Ryzen™ processor

AMD 7th Generation A-Memory series/ Athlon™ processor

2 x DDR4 DIMM sockets supporting up to 32 GB (Please refer "CPU Support List" for more information.) of system memory

Dual channel memory architecture

Support for DDR4

3200(O.C.)/2933(O.C.)/2667*/2400/2133 MHz memory modules

* Actual support may vary by CPU.

Support for ECC Un-buffered DIMM

1Rx8/2Rx8 memory modules (operate in non-ECC mode)

Support for non-ECC Un-buffered DIMM

1Rx8/2Rx8/1Rx16 memory modules

Support for Extreme Memory Profile (XMP) memory modules

(Please refer "Memory Support List" for more information.)

Audio

Realtek® ALC887 codec

High Definition Audio

2/4/5.1/7.1-channel

* To configure 7.1-channel audio, you have to use an HD front panel audio module and enable the multi-channel audio feature through the audio driver.

Support for S/PDIF Out

Expansion Slots

1 x PCI Express x16 slot, running at x16 (PCIEX16)

* Actual support may vary by CPU.

(The PCIEX16 slot conforms to PCI Express 3.0 standard.)

Chipset

AMD A320

Onboard Graphics

Integrated Graphics Processor:

1 x D-Sub port, supporting a maximum resolution of 1920x1200@60 Hz

1 x DVI-D port, supporting a maximum resolution of 1920x1200@60 Hz

* The DVI-D port does not support D-Sub connection by adapter.

1 x HDMI port, supporting a maximum resolution of 4096x2160@24 Hz

* Support for HDMI 1.4 version.

Maximum shared memory of 2 GB

* Actual support may vary by CPU.

LAN

Realtek® GbE LAN chip (10/100/1000 Mbit)

1 x M.2 connector

(Socket 3, M key, type 2242/2260/2280/22110

SATA and PCIe x4/x2* SSD support)

* Actual support may vary by CPU.

* Supports only M.2 SATA SSDs when using an AMD Athlon™ 200-series/ 7th Generation A-series or Athlon™ APU.

4 x SATA 6Gb/s connectors

Support for RAID 0, RAID 1, and RAID 10