

Firma: G Store & Repair doo Adresa: Bul.Mihajla Pupina 10z/3

Telefon: 011 785 66 66

Fax:

PIB: 112029009

E-mail: office@gstore.rs

MB9AM4fGIGABYTE GAVA320M-S2H 1.2

MB AM4 GIGABYTE GA-A320M-S2H 1.2

Šifra: 2504

Kategorija prozivoda: Matične ploče

Proizvođač: GIGABYTE

Cena: 5.982,00 rsd.

CPU

AM4 Socket:

AMD Ryzen™ processor

AMD 7th Generation Aseries/ Athlon™

processor

(Please refer "CPU Support List" for more information.)

Chipset

AMD A320

Onboard Graphics

Integrated Graphics Processor:

1 x D-Sub port,

supporting a maximum

resolution of

1920x1200@60 Hz

1 x DVI-D port,

supporting a maximum

resolution of

1920x1200@60 Hz * **The DMI թեր**ort does

905គមកាល្លាប់ a makimum ខេត្តបានដូច្នេក្រសួង adapter. 4096x2160@24 Hz

* Support for HDMI 1.4

version.

Maximum shared memory of 2 GB

* Actual support may vary by CPU.

LAN

Realtek® GbE LAN chip (10/100/1000 Mbit)

(Pleas

Memo

2 x

sup

of s

Audio

Rea

Expai

| 1 x PCI Express x16 slot, running at x16 (PCIEX16) * Actual support may vary by CPU. (The PCIEX16 slot conforms to PCI Express 3.0 standard.) | 2 x PCI Express x1 slots (The PCI Express x1 slots conform to PCI Express 2.0 standard.) | Storage Interface 1 x M.2 connector (Socket 3, M key, type 2242/2260/2280/22110 SATA and PCIe x4/x2* SSD support) * Actual support may vary by CPU. * Supports only M.2 SATA SSDs when using an AMD Athlon™ 200- series/ 7th Generation A- series or Athlon™ APU. | 4 x SATA 6Gb/s connectors Support for RAID 0, RAID 1, and RAID 10 * Refer to "1-7 Internal Connectors," for the installation notices for the M.2 connector. | USB Chips 2 x ava inte CPU: 4 x on t |
|---|---|--|--|---|
| | | Internal I/O Connectors 1 x 24-pin ATX main power connector | 1 x 8-pin ATX 12V power connector 1 x CPU fan header | Back 1 x |
| | | | 1 x system fan header 1 x M.2 Socket 3 | |
| | | | 4ሚ <u>ዓ</u> ዳተዶ 6Gb/s connectors | |
| | | | 1 x front panel header | |
| | | | 1 x front panel audio head奸DIF Out header | |
| | | | 1 x USB 3.1 Gen 1 ፟ ይ <mark>ፍል ዕ</mark> ኖ ቼ 2.0/1.1 headers | |
| | | | 1 x Trusted Platform Modyled Tel Metaler (2x10 pin, for the GC- TPM2.0 module only) | |
| | | | 1 x Clear CMOS jumper | |
| | | | 1 x chassis intrusion header | |
| | | | | |

I/O Controller

iTE® I/O Controller Chip

H/W I

Voltage detection

Fan speed detection

Overheating warning

Fan fail warning

Fan speed control

* Whether the fan speed

control function is

supported will depend

on the cooler you install.

BIOS 1 x 128 Mbit flash

Use of licensed AMI UEFI BIPS1.0a, DMI 2.7, WfM 2.0, SM BIOS 2.7, ACPI 5.0

Bundle Software Norton® Internet Security (OEM version)

cFosSpeed

Form Factor Micro ATX Form Factor; 24.4cm x 19.5cm Rema

Uniqu

Sup

* A\

in A

by r

Sup

eac

alsc

mot

spe @B

OBUT OBUT BHO Effol

Cold Eas Fas: Gar ON/ Sma Sma Sys: View USE V-To Due to different Linux support condition provided by chipset vendors, please download Linux driver from chipset vendors' website or 3rd party website.

Most hardware/software vendors may no longer offer drivers to support Win9X/ME/2000/XP. If drivers are available from the vendors, we will update them on the GIGABYTE website.