



Firma: G Store & Repair doo
Adresa: Bul.Mihajla Pupina 10z/3
Telefon: 011 785 66 66
Fax:
PIB: 112029009
E-mail: office@gstore.rs

MB s1200 AsRock H510M-HVS

Šifra: 2541

Kategorija proizvoda: Matične ploče

Proizvođač: ASRock

Cena: 8.465 rsd.



Model

Brand	ASRock
Model	H510M-HVS

Supported CPU

CPU Socket Type	LGA 1200
CPU Type	Supports 11th Gen Intel Core Processors Supports 10th Gen Intel Core Processors
Supported CPU Technologies	Turbo Boost Technology 3.0

Chipsets

Chipset	Intel H510
----------------	------------

Onboard Video

Onboard Video Chipset	Supported only by CPU with integrated graphic
------------------------------	---

Memory

Number of Memory Slots	2×288pin
Memory Standard	DDR4 3200 / 2933 / 2800 / 2666 / 2400 / 2133 * * 11th Gen Intel Core (i9 / i7 / i5) support DDR4 up to 3200; Core (i3), Pentium and Celeron support DDR4 up to 2666. * 10th Gen Intel Core (i9 / i7) support DDR4 up to 2933; Core (i5 / i3), Pentium and Celeron support DDR4 up to 2666.
Maximum Memory Supported	64GB
Channel Supported	Dual Channel

Expansion Slots

PCI Express 4.0 x16	1 x PCI Express 4.0 x16* * Actual support may vary by CPU. * Supports NVMe SSD as boot disks.
PCI Express x1	1 x PCI Express 3.0 x1

Storage Devices

SATA 6Gb/s	4 x SATA 6Gb/s
-------------------	----------------

Onboard Audio

Audio Chipset	Realtek ALC897
Audio Channels	7.1 Channels

Onboard LAN

LAN Chipset	Realtek RTL8111H
Max LAN Speed	10/100/1000Mbps

Rear Panel Ports

Back I/O Ports	<ul style="list-style-type: none"> 1 x PS/2 Keyboard Port 1 x PS/2 Mouse Port 1 x D-Sub Port 1 x HDMI Port 2 x USB 3.2 Gen1 Ports (Supports ESD Protection) 4 x USB 2.0 Ports (Supports ESD Protection) 1 x RJ-45 LAN Port with LED (ACT/LINK LED and SPEED LED) HD Audio Jacks: Line in / Front Speaker / Microphone
-----------------------	---

Internal I/O Connectors

Onboard USB	<ul style="list-style-type: none"> 1 x USB 2.0 Header (Supports 2 USB 2.0 ports) (Supports ESD Protection) 1 x USB 3.2 Gen1 Header (Supports 2 USB 3.2 Gen1 ports) (Supports ESD Protection)
Other Connectors	<ul style="list-style-type: none"> 1 x SPI TPM Header 1 x Chassis Intrusion and Speaker Header 1 x CPU Fan Connector (4-pin)* 1 x Chassis/Water Pump Fan Connector (4-pin) (Smart Fan Speed Control)** 1 x Front Panel Audio Connector <p>* The CPU Fan Connector supports the CPU fan of maximum 1A (12W) fan power. ** The Chassis/Water Pump Fan supports the water cooler fan of maximum 2A (24W) fan power. ** CHA_FAN1/WP can auto detect if 3-pin or 4-pin fan is in use.</p>

Physical Spec

Form Factor	Micro ATX
Dimensions (W x L)	7.8" x 7.4"
Power Pin	<ul style="list-style-type: none"> 1 x 24-pin ATX Power Connector 1 x 8-pin 12V Power Connector

Windows Compatibility

Windows 11	Supported
-------------------	-----------

Features

<ul style="list-style-type: none"> Unique Feature: ASRock Super Alloy - Premium 50A Power Choke - Sapphire Black PCB - High Density Glass Fabric PCB ASRock Full Spike Protection (for all USB, Audio, LAN Ports)
