



Firma: G Store & Repair doo  
Adresa: Bul.Mihajla Pupina 10z/3  
Telefon: 011 785 66 66  
Fax:  
PIB: 112029009  
E-mail: [office@gstore.rs](mailto:office@gstore.rs)

---

## MB s1200 ASUS ROG STRIX B460-G Gaming

Šifra: 26085

Kategorija proizvoda: Matične ploče

Proizvođač: ASUS

**Cena: 18.904 rsd.**



Model	ROG STRIX B460-G GAMING
Format	Mixro-ATX Dimenzije : 24.4 x 24.4cm
Čipset	Intel B460
Podnožje/Socket	LGA 1200
CPU podrška	Podrška za 10th generaciju intelovih procesora : - Intel® Core™ i9 processors - Intel® Core™ i7 processors - Intel® Core™ i5 processors - Intel® Core™ i3 processors
Memorijski slotovi	4
Tip memorije	DDR4
Max. količina memorije	MAX : 128GB - Supports Intel® Extreme Memory Profile (XMP)
Radni takt memorije	2933 MHz 2800 MHz 2666 MHz 2400 MHz 2133 MHz
Grafička podrška	Podrška sa intelovim integrisanim UHD grafikama Multi-GPU : Supports AMD 2-Way CrossFireX Technology
Slotovi proširenja	1x PCIe 3.0 x16 slots (supports x16 mode) 1x PCIe 3.0 x16 slots (supports x4 mode) 1x PCIe 3.0 x1 slots

I/O konektori	<p>1x DisplayPort  1x HDMI  1x USB 3.2 Gen 2x2 port(s) (1 x USB Type-C®)  6x USB 3.2 Gen 1  1x USB 2.0 (1 for audio USB Type-C®)  1x USB BIOS FlashBack™ Button(s)  1x HD Audio Connectors  - 7.1-Channel / High Definition Audio CODEC S1220A  1x LAN RJ-45 Port  - Intel® I219-V 1Gb Ethernet</p>
Interni I/O konektori	<p>1x CPU Fan connector(s)  2x Chassis Fan connector(s)  1x AIO_PUMP connector  1x Addressable RGB header  1x AAFP connector  1x Aura RGB Strip Headers  1x S/PDIF out header(s)  1x 24-pin EATX Power connector(s)  1x 8-pin ATX 12V Power connector(s)  1x Clear CMOS jumper(s)  1x System panel connector  1x COM port(s) connector(s)</p> <p>1x USB 3.2 Gen 1 (up to 5Gbps) connector(s)  support(s) additional 2 USB 3.2 Gen 1 port(s)</p> <p>2x USB 2.0 connector(s)  support(s) additional 4 USB 2.0 port(s)</p> <p>6x SATA 6Gb/s connector(s)  - Support for RAID 0, RAID 1, RAID 5, and RAID 10</p> <p>1x M.2 Socket 3, with M Key  Type 2242/2260/2280 (PCIe 3.0 x4 and SATA modes) storage devices support*2</p> <p>1 x M.2_2 socket 3, with M key  type 2242/2260/2280 storage devices support (PCIe 3.0 x 4 mode)</p> <p>1x M.2 with E key for Wi-Fi module</p>