



Firma: G Store & Repair doo
Adresa: Bul.Mihajla Pupina 10z/3
Telefon: 011 785 66 66
Fax:
PIB: 112029009
E-mail: office@gstore.rs

MB AM4 ASUS TUF B450M-PRO GAMING

Šifra: 26115

Kategorija proizvoda: Matične ploče

Proizvođač: ASUS



Cena: 11.285 rsd.

Podnožje:	AMD® AM4
Čipset:	AMD® B450
Tip procesora:	AMD
Format ploče:	Micro ATX
Podržani procesori:	AMD AM4 Socket AMD Ryzen™ druge generacije/ Ryzen™ sa Radeon™ Vega grafikom/ Athlon sa Radeon™ Vega grafikom / Ryzen™ prve generacije. Podržava CPU sa do 8 jezgra
Podržana memorija:	DDR4
Memorija:	4 x DIMM, maksimalni podržani kapacitet 64GB, DDR4 3533(O.C)/3466(O.C.)/3200(O.C.)/3000(O.C.)/2800(O.C.)/2666/2400/2133 MHz nebaferovane memorije Dvokanalna memorijska arhitektura Podrška za ECC memoriju (ECC mod) zavisi od procesora.
Multi-GPU podrška:	Podržava AMD CrossFireX™ Tehnologiju
Integrisana grafička karta:	Podržava integrisanu grafiku u procesorima AMD Ryzen™ sa Radeon™ Vega grafikom/ Athlon™ sa Radeon™ Vega grafikom Dva izlaza: HDMI / DVI-D port - Podržava HDMI 2.0b sa maksimalnom rezolucijom 4096 x 2160 @ 60 Hz - Podržava DVI-D sa maksimalnom rezolucijom 1920 x 1200 @ 60 Hz
Slotovi za proširenje:	AMD Ryzen™ prva i druga generacija 1 x PCIe 3.0/2.0 x16 (x16 mode) AMD Ryzen™ sa Radeon™ Vega Grafikom 1 x PCIe 3.0/2.0 x16 (x8 mode) AMD Athlon™ sa Radeon™ Vega Grafikom 1 x PCIe 3.0/2.0 x16 (max at x4 mode) AMD B450 chipset 1 x PCIe 2.0 x16 (max at x4 mode) 1 x PCIe 2.0 x1
Skladište:	AMD Ryzen™ 2nd Generation/ Ryzen™ with Radeon™ Vega Graphics/ Ryzen™ 1st Generation Processors : 1 x M.2 Socket 3, with M key, type 2242/2260/2280 storage devices support (SATA & PCIE 3.0 x 4 mode)*1 AMD Athlon™ with Radeon™ Vega Graphics Processors : 1 x M.2 Socket 3, with M key, type 2242/2260/2280 storage devices support (SATA mode)*1 AMD Ryzen™ druga generacija/ Ryzen™ sa Radeon™ Vega Grafikom / Athlon™ sa Radeon™ Vega Grafikom/ Ryzen™ prve generacije : 2 x SATA 6Gb/s port(s) Podržava Raid 0, 1, 10 AMD B450 chipset : 1 x M.2 Socket 3, with M Key, type 2242/2260/2280 storage devices support (SATA & PCIE 3.0 x 2 mode)*2 4 x SATA 6Gb/s port(s) Podržava Raid 0, 1, 10
Mrežna karta:	Realtek® RTL8111H TUF LANGuard

Zvučna karta:	Realtek® ALC S1200A 8-Channel High Definition Audio CODEC Audio karakteristike: - Ekskluzivni DTS Custom za gejmerske slušalice - Audio Shielding: obezbeđuje preciznu analogno/digitalnu separaciju i značajno smanjuje multilateralnu interferenciju - Namenski audio PCB slojevi: odvojeni slojevi za levi i desni kanal kako bi se sačuvao kvalitet osetljivih audio signala - Premijum japanski kondenzatori: obezbeđuju topao i prirodan zvuk sa izuzetnom vernošću i jasnoćom - Audio zaštita - Efektivni štiti čuva integritet audio signala kako bi se obezbedio najbolji kvalitet
USB:	AMD Ryzen™ 2nd Generation/ Ryzen™ with Radeon™ Vega Graphics/ Athlon™ with Radeon™ Vega Graphics/ Ryzen™ 1st Generation Processors : 2 x USB 3.1 Gen 1 port(s) (2 at back panel, , Type-A) AMD Ryzen™ 2nd Generation/ Ryzen™ with Radeon™ Vega Graphics/ Athlon™ with Radeon™ Vega Graphics/ Ryzen™ 1st Generation Processors : 1 x USB 3.1 Gen 1 port (1 na zadnjem panelu, USB Type-C™) AMD B450 chipset : 1 x USB 3.1 Gen 2 port (1 na zadnjem panelu) AMD B450 chipset : 2 x USB 3.1 Gen 1 porta (2 preko internih konektora) AMD B450 chipset : 6 x USB 2.0 porta (2 na zadnjem panelu, 4 preko internih konektora)
Konektori na zadnjoj strani:	1 x PS/2 keyboard/mouse combo port(s) 1 x DVI-D 1 x HDMI 1 x LAN (RJ45) port(s) 1 x USB 3.1 Gen 2 Type-A, 1 x USB 3.1 Gen 1 USB Type-C™ 2 x USB 3.1 Gen 1 (blue) Type-A 2 x USB 2.0 3 x Audio jack(s)
Interni konektori:	2 x Aura RGB Strip Header 1 x USB 3.1 Gen 1(up to 5Gbps) connector(s) support(s) additional 2 USB 3.1 Gen 1 port(s) (19-pin) 2 x USB 2.0 connector(s) support(s) additional 4 USB 2.0 port(s) 2 x M.2 Socket 3 with M key, type 2242/2260/2280 storage devices support 6 x SATA 6Gb/s connector(s) 1 x CPU Fan connector(s) (1 x 4 -pin) 2 x Chassis Fan connector(s) (2 x 4 -pin) 1 x S/PDIF out header(s) 1 x 24-pin EATX Power connector(s) 1 x 8-pin ATX 12V Power connector(s) 1 x Front panel audio connector(s) (AAFP) 1 x System panel(s) 1 x Clear CMOS jumper(s) 1 x COM port header 1 x Speaker connector
BIOS:	128 Mb Flash ROM, UEFI AMI BIOS, PnP,SM BIOS 3.1, ACPI 6.1, Multilanguage BIOS, ASUS EZ Flash 3, ASUS CrashFree BIOS 3, F3 My Favorite, Last Modified log, F12 PrintScreen, F4 AURA ON/OFF, F9 Search and ASUS DRAM SPD (Serial Presence Detect) memory information
Ostalo:	ASUS TUF PROTECTION - ASUS SafeSlot: Protect your graphics card Investment - ASUS Overvoltage Protection: World-class circuit-protecting power design - ASUS Stainless-Steel Back I/O: 3X corrosion-resistance for greater durability! - ASUS DIGI+ VRM: Precision control for stable power - ASUS LANGuard: Protects against LAN surges, lightning strikes and static-electricity discharges! AURA : - Aura Lighting Control - Aura RGB Strip Headers ASUS Exclusive Features : - AI Suite 3 - Ai Charger - PC Cleaner ASUS Quiet Thermal Solution : - Stylish Fanless Design Heat-sink solution & MOS Heatsink - ASUS Fan Xpert 2+ ASUS EZ DIY : - ASUS CrashFree BIOS 3 - ASUS EZ Flash 3 - ASUS UEFI BIOS EZ Mode ASUS Q-Design : - ASUS Q-Slot - ASUS Q-DIMM