



Firma: G Store & Repair doo  
Adresa: Bul.Mihajla Pupina 10z/3  
Telefon: 011 785 66 66  
Fax:  
PIB: 112029009  
E-mail: [office@gstore.rs](mailto:office@gstore.rs)

---

## MB AM4 MSI MAG X570 TOMAHAWK WIFI

Šifra: 2615

Kategorija proizvoda: Matične ploče

Proizvođač: MSI



**Cena: 30.177 rsd.**

Podnožje:	AMD® AM4
Čipset:	AMD® X570
Tip procesora:	AMD
Format ploče:	ATX
Podržani procesori:	- 2nd i 3rd Gen AMD Ryzen / Ryzen sa Radeon Vega grafikom, i 2nd Gen AMD Ryzen sa Radeon grafičkim desktop procesorima za podnožje AM4
Podržana memorija:	DDR4
Memorija:	- 4x DDR4 memorijska slota, podržava do 128GB - 3rd Gen AMD Ryzen procesora podržava DDR4 1866/ 2133/ 2400/ 2667/ 2800/ 2933/ 3000/ 3066/ 3200 Mhz by JEDEC, i 2667/ 2800/ 2933/ 3000/ 3066/ 3200/ 3466/ 3600/ 3733/ 3866/ 4000/ 4133/ 4266/ 4400/ 4533/ 4600+ Mhz by A-XMP OC MODE - 2nd Gen AMD Ryzen procesora, 1st i 2nd Gen AMD Ryzen sa Radeon Vega grafičkim procesorima podržava DDR4 1866/ 2133/ 2400/ 2667/ 2800/ 2933/ 3000/ 3066/ 3200 Mhz by JEDEC, and 2667/ 2800/ 2933/ 3000/ 3066/ 3200/ 3466+ Mhz by A-XMP OC MODE - Dual channel memory architecture - Podržava non-ECC UDIMM memoriju - Podržava ECC UDIMM memoriju (non-ECC mode) - Podržava un-buffered memoriju
Multi-GPU podrška:	- Podržava 2-Way AMD CrossFire tehnologiju
Integrirana grafička karta:	- 1x HDMI 1.4 port, podržava maksimalnu rezoluciju od 4096x2160 @24Hz - Maksimalna deljena memorija 2048 MB
Slotovi za proširenje:	- 1x PCIe 4.0/3.0 x16 slot (PCI_E1) - 3rd Gen AMD Ryzen podržava PCIe 4.0 x16 mod - 2nd Gen AMD Ryzen podržava PCIe 3.0x16 mod - Ryzen sa Radeon Vega grafikom i druga generacija AMD Ryzen sa Radeon grafikom podržava PCIe 3.0 x8 mod - 1x PCIe 4.0/3.0 x16 slot (PCI_E3), supports x4 mod - 2x PCIe 3.0 x1 slot
Skladište:	- 6x SATA 6Gb/s portova (from AMD® X570 Chipset) - 2x M.2 slota (Key M) 1 - M2_1 slot (from AMD® Processor) - Podržava PCIe 4.0 x4 (3rd Gen AMD Ryzen) - Podržava PCIe 3.0 x4 (2nd Gen AMD Ryzen / Ryzen sa Radeon Vega grafikom i 2nd Gen AMD Ryzen sa Radeon grafikom) - Podržava 2242/ 2260/ 2280/ 22110 storage uređaje - M2_2 slot (from AMD® X570 Chipset) - Podržava PCIe 4.0 x4 (3rd Gen AMD Ryzen) - Podržava PCIe 3.0 x4 (2nd Gen AMD Ryzen / Ryzen sa Radeon Vega grafikom i 2nd Gen AMD Ryzen sa Radeon grafikom) - Podržava SATA 6Gb/s - Podržava 2242/ 2260/ 2280 storage uređaje

Mrežna karta:	- 1x Realtek® 8125B 2.5Gbps LAN kontroler Intel® Wi-Fi 6 AX200 - Podrška 802.11 a/b/g/n/ac/ax, MU-MIMO Rx, 2.4GHz-5GHz (160MHz) up to 2.4Gbps - Podrška Bluetooth 5.1 - Wireless module je preinstaliran u M2_WIFI1 (Key-E) slot
Zvučna karta:	Realtek® ALC1200 Codec - 7.1-Channel High Definition Audio - Podrška Optical S/PDIF output
USB:	AMD® X570 Chipset - 3x USB 3.2 Gen 2 10Gbps porta (2 Type-A porta na zadnjem panelu, 1 Type-C interni konektor) - 4x USB 3.2 Gen 1 5Gbps porta dostupna putem internog USB 3.2 Gen 1 5Gbps konektora - 6x USB 2.0 porta (2 Type-A porta na zadnjem panelu, 4 porta dostupna putem internog USB 2.0 konektora) AMD® Processor - 2x USB 3.2 Gen 2 10Gbps (3rd Gen AMD Ryzen) ili USB 3.2 Gen 1 5Gbps (2nd Gen AMD Ryzen / Ryzen sa Radeon Vega grafikom i 2nd Gen AMD Ryzen sa Radeon grafikom) porta (1x Type-A & 1x Type-C) na zadnjem panelu - 2x USB 3.2 Gen 1 5Gbps Type-A porta na zadnjem panelu
Konektori na zadnjoj strani:	- Keyboard / Mouse - Wireless / Bluetooth - USB 3.2 Gen 1 5Gbps Type A -USB 3.2 Gen 2 10Gbps Type A - 2.5G LAN port - Audio Connectors - Flash BIOS button - USB 2.0 - HDMI port - USB 3.2 Gen 2 10Gbps Type C - USB 3.2 Gen 2 10Gbps Type A - Optical S/PDIF out
Interni konektori:	- 1x 24-pin ATX main power connector - 1x 8-pin ATX 12V power connector - 1x 4-pin ATX 12V power connector - 6x SATA 6Gb/s connectors - 2x USB 2.0 connectors (supports additional 4 USB 2.0 ports) - 2x USB 3.2 Gen 1 5Gbps connectors (supports additional 4 USB 3.2 Gen 1 5Gbps ports) - 1x USB 3.2 Gen 2 10Gbps Type-C Port - 1x 4-pin CPU fan connector - 1x 4-pin water-pump connector - 4x 4-pin system fan connectors - 1x Front panel audio connector - 2x System panel connectors - 1x TPM module connector - 1x Serial port connector - 1x Clear CMOS jumper - 1x Chassis Intrusion connector - 2x 4-pin RGB LED connectors - 2x 3-pin RAINBOW LED connectors - 4x EZ Debug LEDs - 1x TBT connector 1 - 1x RTD3 connector
BIOS:	- 1x 256 Mb flash - UEFI AMI BIOS - ACPI 6.1, SM BIOS 2.8 - Multi-language