



Firma: G Store & Repair doo
Adresa: Bul.Mihajla Pupina 10z/3
Telefon: 011 785 66 66
Fax:
PIB: 112029009
E-mail: office@gstore.rs

Netis WF2190 AC1200 WIRELESS DUAL BAND USB ADAPTER

Šifra: 28764

Kategorija proizvoda: Mrežne kartice

Proizvođač: NETIS

Cena: 3.253 rsd.



AC1200 Wireless Dual Band USB Adapter

The netis WF2190 is designed to connect a desktop or notebook computer to a wireless network and access high-speed Internet connection. It's compatible with 802.11a/b/g/n/ac devices and provides the wireless transfer speed up to 2.4GHz 300Mbps or 5GHz 867Mbps, offering a better performance on online gaming, HD video streaming, and VoIP phone calling. With the 802.11n MIMO and 802.11ac technology, it ensures a strong and stable wireless connection and allows you to enjoy the wireless freedom around your home. Moreover, it features with a WPS button which helps you easily setup a secure wireless connection in a snap.

Maximum speed up to 2.4GHz 300Mbps and 5GHz 867Mbps.

Integrate the latest 802.11 AC technology, use in 2.4 G or 5 G Networks.

2*5dBi detachable antennas allowing for stronger antenna upgrades.

Advanced security feature with the latest WPA2 encryption to protect the network.

Easy connection to a wireless network at a push of the WPS button.

Access Point feature to set up a Wi-Fi hotspot to share the Internet.

Easy to install and configure with the setup CD and utility.

Wireless

Standards IEEE 802.11a/b/g/n/ac

Signal Rate 2.4GHz Up to 300Mbps

5 GHz UP to 867Mbps

Frequency Range 2.4-2.4835GHz;5.180-5.825GHz

Wireless Mode Station, Access Point

Wireless Security Support 64/128-bit WEP, WPA-PSK/WPA2-PSK, 802.1 X

Hardware

Port USB 3.0

Button WPS

Dimensions (L xW x H) 92.5 x 27 x 15mm

Others

Certification FCC, CE, KC

System Requirements

Windows XP (32/64bits),

Windows Vista (64/86bits),

Windows 7 (64/86bits),

Windows 8 (64/86bits), Windows 8.1 (64/86bits), Win 10(32/64bits)

MAC 10.4/10.5/10.6/10.7/10.8/10.9/10.10/10.11

Linux as Ubuntu 14.04/13.10/12.04/11.04

Environment Operating Temperature: 0c~40c

Storage Temperature: -40c?~70c

Operating Humidity: 10%~90% non-condensing