



Firma: G Store & Repair doo  
Adresa: Bul.Mihajla Pupina 10z/3  
Telefon: 011 785 66 66  
Fax:  
PIB: 112029009  
E-mail: [office@gstore.rs](mailto:office@gstore.rs)

---

## Matična ploča 1200 Biostar H410MH VGAHDMIM.2

---

Šifra: 28788

Kategorija proizvoda: Matične ploče

Proizvođač: INTEL

**Cena: 7.728 rsd.**



Tip procesora:	Intel
Podnožje:	Intel®; 1200
Čipset:	Intel®; H410
Format ploče:	Socket L1200 for 10th Gen Intel Core™, Pentium and Celeron processors * 10th Generation Intel Core™ Processor Family only support 400-Series * Please refer to <a href="http://www.biostar.com.tw">www.biostar.com.tw</a> for CPU support list.
Podržani procesori:	
Podržana memorija:	Supports Dual Channel DDR4 DDR4 2133 2400 2666 2800 2933 2 x DDR4 DIMM Memory Slots, Max. Supports up to 64 GB Memory Each DIMM supports non-ECC 481632GB DDR4 module * Please refer to Memory Support List for more information. Core (i9i7) support DDR4 up to 2933 MHz; Core (i5i3), Pentium and Celeron support DDR4 up to 2666 MHz.
Memorija:	
Integrirana grafička karta:	By CPU model Supports DX12 Supports HDCP
Slotovi za proširenje:	2 x PCIe 2.0 x 1 Slots, 1 x PCIe 3.0 4 x SATA III Connectors (6Gbs) 1 x M.2 (M Key) Socket Supports M.2 Type 2242 2260 2280 SSD module Supports PCIe 2.0 x 2 (10Gbs) -NVMe AHCI SSD and SATA III (6Gbs) SSD * When using NVMeAHCI PCIe SSD module on M.2(PCle-M2_1)slot, all of SATA connectors will be enabled. * When using SATA SSD module on M.2(PCle-M2_1)slot, the SATA_1 connector will be disabled.
Storage:	
Mrežna karta:	RTL8111H 10 100 1000 Mbs auto negotiation, Half Full duplex capability
Zvučna karta:	ALC887 7.1 Channels, High Definition Audio
USB:	4 x USB 3.2(Gen1) ports (2 on rear IOs and 2 via internal headers) 6 x USB 2.0 ports (4 on rear IOs and 2 via internal headers)
Konektori na zadnjoj strani:	1 x PS2 Keyboard 1 x PS2 Mouse 1 x HDMI Port 1 x VGA Port 2 x USB 3.2 (Gen1) Ports 4 x USB 2.0 Ports 1 x LAN port 3 x Audio Jack x USB 2.0 Header (each header supports 2 USB 2.0 ports) 1 x USB 3.2 (Gen1) Header (each header supports 2 USB 3.2 (Gen1) ports) 1 x 8-Pin Power Connector 1 x 24-