



Firma: G Store & Repair doo
Adresa: Bul.Mihajla Pupina 10z/3
Telefon: 011 785 66 66
Fax:
PIB: 112029009
E-mail: office@gstore.rs

Tenda TEG1124P-24-250W LAN 24-Port
10/100/1000M Base-T Ethernet ports Desktop or
rack mount switch



Šifra: 37113

Kategorija proizvoda: Switch uređaji

Proizvođač: TENDA

Cena: 37.434 rsd.

TEG1124P-24-250W je Tenda PoE switch koji nudi 24 10/100/1000 Mbps Base-TKS RJ45 portova. Portovi 1-24 su u skladu sa IEEE 802.3af standardom (maksimalna PoE snaga: 15,4W) i 802,3at standardom (maksimalna snaga PoE: 30W). Switch nudi maksimalnu izlaznu snagu od 225W i može da napaja i razmenjuje podatke sa AP, IP kamerama i IP telefonima preko CAT5 kablova. Omogućava i jednostavne nacine upravljanja kao što su CCTV, VLAN i izolacija kako bi se smanjili troškovi kablova IP terminala kao što su AP i IP kamere.

Standard&Protocol: IEEE 802.3/IEEE 802.3u/IEEE 802.3ab/IEEE 802.3x/IEEE 802.3af/IEEE 802.3at

Indicator: 24*Link/Act per device

24*PoE per device

1*Power per device

Interface: 24 10/100/1000Base-T ports(Data/Power)

Lightning Protection: 6KV

Store & Forward: Yes

exchange capacity: 48 Gbp

Packet Forwarding Rate: 35.6Mpps

RAM Data Buffer: 4Mb

MAC Address Table: 4K

PoE supply management: Port 1-24 support IEEE802.3at/af PoE standard

PoE through pin1 2 4 5 +/3 6 7 8 -

Input Power AC: 100-240V~50/60Hz

Dimension: 440*178*44mm(W x D x H)

Power Consumption in full con guration: 250W

PoE Max Power Supply: 225W

Port Features: Standard: the switch functions as a common unmanaged switch and all the ports of the switch can communicate with each other.

CCTV: the port cache is optimized and PoE ports 1-8 have higher priorities over the other ports. All the ports of the switch can communicate with each other.

VLAN: ports 1 to 22 are isolated from each other, but can communicate with ports 23 and 24(uplink ports) respectively.

Isolation: ports 1 to 12 and Ports 13 to 24 belong to two di erent VLAN.This mode can be used to isolate supervision network and wireless network to make them not interfere with each other.

Environment: Operating Temperature: 0?~40? (32?~104?)

Storage Temperature: -40?~70? (-40?~158?)

Operating Humidity: 10%~90% non-condensing

Storage Humidity: 5%~90% non-condensing