



Firma: G Store & Repair doo  
Adresa: Bul.Mihajla Pupina 10z/3  
Telefon: 011 785 66 66  
Fax:  
PIB: 112029009  
E-mail: [office@gstore.rs](mailto:office@gstore.rs)

---

## Tenda TEG1116P-16-150W LAN 16-Port 10/100/1000M Base-TX Ethernet ports Switch



Šifra: 37117

Kategorija proizvoda: PoE Adapteri

Proizvođač: TENDA

**Cena: 26.578 rsd.**

TEG1116P-16-150W is a Tenda PoE Switch that offers 16 10/100/1000Mbps Base-TX RJ45 ports 1-16 comply with IEEE 802.3af standard (maximum PoE power output: 15.4 W) and 802.3at standard (maximum PoE power output: 30 W). The switch offers a maximum PoE power output of 135W and can supply power to and exchange data with APs, IP cameras and IP phones through CAT5 cables. It also provides simple management modes such as CCTV, VLAN and isolation to help reduce cabling costs of IP terminals like APs and IP cameras.

Standard&Protocol IEEE 802.3/IEEE 802.3u/IEEE 802.3ab/IEEE 802.3x/IEEE 802.3af/IEEE 802.3at

Indicator16\*Link/Act per device

16\*PoE per device

1\*Power per device

Interface16 10/100/1000 Base-T ports(Data/Power)

Lightning Protection 6KV

Store & Forward Yes

exchange capacity 32 Gbps

Packet Forwarding Rate 23.6Mpps

RAM Data Buffer4Mb

MAC Address Table 4K

PoE supply management Port 1-16 support IEEE802.3at/af PoE standard

PoE through pin1 2 4 5 +

3 6 7 8 -

Input Voltage AC: 100-240V~50/60Hz

Dimension 294\*178\*44mm ( W x D x H )

Power Consumption in full con guration:150W

PoE Max Power Supply:135W

Port FeaturesStandard: the switch functions as a common unmanaged switch and all the ports of the switch can communicate with each other.

CCTV: the port cache is optimized and PoE ports 1-8 have higher priorities over the other ports. All the ports of the switch can communicate with each other.

VLAN: ports 1 to 14 are isolated from each other, but can communicate with ports 15 and 16 (uplink ports) respectively.

Isolation: ports 1 to 8 and Ports 9 to 16 belong to two di erent VLAN.This mode can be used to isolate supervision network and wireless network to make them not interfere with each other.

Environment Operating Temperature: 0?~40? (32?~104?)

Storage Temperature: -40?~70? (-40?~158?)

Operating Humidity: 10%~90% non-condensing

Storage Humidity: 5%~90% non-condensing