



Firma: G Store & Repair doo
Adresa: Bul.Mihajla Pupina 10z/3
Telefon: 011 785 66 66
Fax:
PIB: 112029009
E-mail: office@gstore.rs

IP-COM IUAP-AC-M Access Point Indoor/Outdoor
WiFi Dual-Band 2,4+5GHz AP, Client+AP, MU-
MIMO, 200m

Šifra: 37151

Kategorija proizvođa: Ruteri

Proizvođač: IP-COM



Cena: 10.097 rsd.

The gigabit dual-band indoor/outdoor access point iUAP-AC-M offers a concurrent data rate as high as 1167 Mbps. Equipped with 2 omni-directional high-gain antennas, iUAP-AC-M provides a maximum coverage radius of 200 meters. iUAP-AC-M can be installed either on the wall or around a pole. iUAP-AC-M can meet different requirements by connecting antennas of different specifications to the standard RP-SMA connectors. With the IP65 enclosure, iUAP-AC-M is designed for wireless coverage in factories, warehouses and other harsh outdoor environments.

Durable IP65 enclosure for outdoor Wi-Fi applications

MU-MIMO technology for high throughput

Concurrent dual-band data rate up to 1167 Mbps (2.4 GHz: 300 Mbps; 5 GHz: 867 Mbps)

Detachable antennas and 2 RP-SMA connectors

Coverage radius of 200 meters

Mounting Pole Mounting and Wall Mounting

Dimensions 194.7*83*42.1 mm

Hardware Specifications

Frequency band 2.4 GHz, 5 GHz

Wireless standards IEEE 802.11a, IEEE 802.11b, IEEE 802.11g, IEEE 802.11n, IEEE 802.11ac

2.4 GHz data rate 1 - 300 Mbps

5 GHz data rate 6 - 867 Mbps

Ethernet port 1*10/100/1000 Base-TX port

Button 1*Reset

LED indicator 1*SYS

Waterproof level IP65

Lightning protection 6000 V

Max. power consumption 11.5 W (Full-load)

Power supply standard IEEE 802.3af/at & 24V, 0.5A Passive PoE

Antenna 2*5dBi,RP-SMA Connector

2.4 GHz Max. output power 26 +/- 1.5 dBm

5 GHz Max. output power 26 +/-1.5 dBm

802.11b RX sensitivity -93 dBm

2.4 GHz 802.11n (MCS7) RX sensitivity -72 dBm

5 GHz 802.11a RX sensitivity -93 dBm

5 GHz 802.11n (MCS7) RX sensitivity -74 dBm

Software Specifications

Operating modes AP, Client+AP

Hide SSID Supported

Max. No. of SSID 2.4 GHz: 8

5 GHz: 4

Max. connected clients 2.4 GHz: 128

5 GHz: 256