



Firma: G Store & Repair doo  
Adresa: Bul.Mihajla Pupina 10z/3  
Telefon: 011 785 66 66  
Fax:  
PIB: 112029009  
E-mail: [office@gstore.rs](mailto:office@gstore.rs)

---





Tenda B6 5GHz, 300Mbps,  
AP/Station/WISP/P2MP/WDS Repeater/Router

---

Šifra: 37163

Kategorija proizvoda: Ruteri

Proizvođač: TENDA



**Cena: 8.690 rsd.**

B6 5GHz 11n 300Mbps Basestation is designed for PtP and PtMP solutions for rural wireless connectivity and CCTV surveillance. Features with two RP-SMA enable it to pair with dish antenna or sector antenna to establish PtP backhaul connection and P2MP link. It adopts Tenda TDMA (Time Division Multiple Access) proprietary protocol--TD-MAX to improve performance and capacity. The auto-bridging technology enable it easy to setup for both business and home users.

Dimension 194.7\*83\*42.1mm

Deployment Pole Mount

Application Scenarios PtP, PtMP for rural wireless connectivity and CCTV surveillance

Frequency Range 5GHz

Standard&Protocol IEEE 802.11a/n

Private TDMA Protocol TD-MAX

Maximum wireless speed 300Mbps

Interface 1\*10/100Mbps Ethernet Port

Antenna 2\*RP-SMA

Reset Button1

GND1

Power Consumption 8.5W

Waterproof Level IP65

LED indicator PoE/LAN,LED1,LED2,LED3

Power Method 24V0.5A Passive PoE

Lightning Protection 6000V

Passive PoE power supply Passive power over ethernet via PoE/LAN ( 4,5pins  
-7,8pins)

Voltage range: 21-25V DC

Reception SensitivityMCS0: -96dbm

MCS7: -72dbm

Operating Mode: AP/Station/WISP/P2MP/WDS Repeater/Router

Enable/Disable Wireless RadioSupport

SSID HiddenSupport

SSID IsolationSupport

Channel10/20/30/40MHz

Client Limitation For SSID Support

Wireless Access Control Support

Weak Signal Client Limitation Support

Transmit PowerAdjustable power by 1dBm

WMM Capable Support

APSD Capable Support

Wireless Security 64/128 WEP,WPA-PSK,WPA2-PSK,WPA&WPA2-PSK,WPA,WPA2

Transparent Bridge Support

VLAN Tagging for SSID Support

DHCP Server Support