



Firma: G Store & Repair doo
Adresa: Bul.Mihajla Pupina 10z/3
Telefon: 011 785 66 66
Fax:
PIB: 112029009
E-mail: office@gstore.rs

Tenda O1 outdoor Point to Point CPE 2.4GHz 300Mbps, 8dBi, 500m

Šifra: 37948

Kategorija proizvoda: Ruteri

Proizvođač: TENDA



Cena: 4.979 rsd.

O1 2.4GHz Outdoor CPE is designed to WISP CPE solutions and long distance wireless network solutions for video surveillance and data transmission. It features with 8dBi directional antenna to provide an efficient way to pick up and maintain a stable signal for a wireless network. Adopt of auto-bridging technology,two CPE can connect to each other automatically to make it easy to setup.

- 2.4GHz 11n 300Mbps
- 8dbi directional antenna
- IP65 waterproof enclosure
- AP,Station,WISP operating mode supported
- Up to 30 meters of flexible deployment with included PoE Injector

500m+ Wireless Data Transmission

O1 integrates with a 8dBi directional antenna to provide an optimized transmission quality. It picks up and maintains a stable signal for a wireless network connection ranging up to 500 meters.

O1 adopts of auto-bridge technology,two cpe can connect to each other when you power on them face to face. It is very easy to setup.

Professional Outdoor Design

Equipped with IP65 waterproof enclose and high quality hardware design, O1 can work in various weather conditions, such as sunshine, rainfall or extremely low/high temperature environment .

Multiple Application Scenarios

Long-Distance Wireless Connection

One work as AP mode and another work as Station mode to create a long distance wrieless connecton for video surveillanci and data transmission.

WISP(Client+Router) Mode

Wirelessly connect to WISP station/hotspot to share Internet to local wireless and wired network.

Smart Signal Indicator LED

Three signal LED Lights represent the currently signal strength that O1 receives from peer device.It is helpful to find the right location to deploy the device and achieve a better performance.

Dimension 193.5*80*67.5mm

Deployment Pole Mount/Wall Mount

Application Scenarios PtP and PtMP wireless connection for Privated ISP access or CCTV Surveillance

Frequency Range 2.4GHz

Compliant Standards IEEE 802.11b/g/n

Maximum Wireless Rate 300Mbps

Interfaces 1*10/100Mbps Ethernet Port

Antenna Polarization Dual Polarization

Antennas Gain 8dbi