



Firma: G Store & Repair doo
Adresa: Bul.Mihajla Pupina 10z/3
Telefon: 011 785 66 66
Fax:
PIB: 112029009
E-mail: office@gstore.rs

Dahua Mrežni kabal Cat5 DH-PFM920I-5EUN UTP BAKARNI 305m

Šifra: 43793

Kategorija proizvoda: Mrežni kablovi

Proizvođač: DAHUA



Cena: 19.403 rsd.

- 305 m (1000 ft)/karton UTP CAT5e, napajanje preko Ethernet, kompatibilan sa jednim kablom
- Bakarni provodnik oxygen-free visoke cistoce
- Prilagodeni PVC spoljni omotac; CE CPR Eca sertifikovana klasa otpornosti na vatru

Material: Oxygen free copper (99.97% purity)

Diameter: 0.45 mm \pm 0.01 mm

Insulation

Material: HDPE

Min. Average Thickness: 0.18 mm

Diameter: 0.81mm \pm 0.1mm

Color (4 Pairs): Blue, white/blue; orange, white/orange; green, white/green; brown, white/brown

Rip Cord

Material: Polyester

Specification: 500D

Sheath

Material: PVC

Min. Average Thickness: 0.5 mm

Diameter: 4.7 mm \pm 0.3 mm

Color: White

Electrical

Max. DC Resistance of a Single Conductor: 120/100 m

Min. Insulation Resistance: 5000MO \cdot km

Max. DC Resistance Unbalance: 2% (pair intra), 4% (pairs inter)

Dielectric Strength: No breakdown with 1KV DC for 1 min

Transmission

Characteristic Impedance: 100 \pm 150

Near End Cross Talk: =35.30 dB/100 m@100 MHz

Max. Attenuation: 24.2 dB/100 m@100 MHz

Return Loss: =20.1 dB/100 m@100 MHz

Mechanical

Tensile Strength:

Sheath=13.5 MPa, insulation=16 MPa

Elongation at Break: Sheath=150%, insulation=300%

Installation Bending Radius: >8 times of outer cable diameter

Conductor Elongation at Break: =10%

Environmental