



Firma: G Store & Repair doo
Adresa: Bul.Mihajla Pupina 10z/3
Telefon: 011 785 66 66
Fax:
PIB: 112029009
E-mail: office@gstore.rs

MB s1700 Gigabyte B660M GAMING X AX

Šifra: 50330

Kategorija proizvoda: Matične ploče

Proizvođač: GIGABYTE

Cena: 22.029 rsd.



DDR4 socket. Support for 12th Generation Intel® Core™, Pentium® Gold and Celeron® Processors* Support for L3 cache varies with CPU DDR4 4400(O.C.) / 4300(O.C.) / 4266(O.C.) / 4133(O.C.) / 4000(O.C.) / 3866(O.C.) / 3800(O.C.) / 3733(O.C.) / 3666(O.C.) / 3600(O.C.) / 3466(O.C.) / 3400(O.C.) / 3333(O.C.) / 3300(O.C.)

/3200/3000/2933/2666/2400/2133 MHz memory modules

4 x DDR DIMM sockets supporting up to 128 GB (32 GB single DIMM capacity) of system memory

Dual channel memory architecture

Support for ECC Unbuffered DIMM 1Rx8/2Rx8 memory modules (operate in non-ECC mode)

Support for non-ECC Unbuffered DIMM 1Rx8/2Rx8/1Rx16 memory modules

Support for Extreme Memory Profile (XMP) memory modules

(Please refer "Memory Support List" for more information.)

Audio

Realtek® Audio CODEC

High Definition Audio

2/4/5.1/7.1-channel

* To configure 7.1-channel audio, you need to open the audio software and select Device advanced settings > Playback Device to change the default setting first. Please visit GIGABYTE's website for details on configuring the audio software.

Support for S/PDIF Out

Wireless Communication module

Intel® Wi-Fi 6 AX200 (For PCB rev. 1.0)

WiFi a, b, g, n, ac, ax,

Chipset

Intel® B660 Express

Chipset

Onboard Graphics

Integrated Graphics Processor-Intel® HD Graphics support:

1 x HDMI port, supporting a maximum resolution of 4096x2160@60 Hz

* Support for HDMI 2.1 version and HDCP 2.3.

** Support native HDMI 2.1 TMDS compatible ports.

1 x DisplayPort, supporting a maximum resolution of 4096x2304@60 Hz

* Support for DisplayPort 1.2 version and HDCP 2.3

(Graphics specifications may vary depending on CPU support.)

LAN

2.5GbE LAN chip (2.5

Gbps/1 Gbps/100 Mbps)