



Firma: G Store & Repair doo
Adresa: Bul.Mihajla Pupina 10z/3
Telefon: 011 785 66 66
Fax:
PIB: 112029009
E-mail: office@gstore.rs

MB s1700 GIGABYTE B660 AORUS MASTER DDR5

Šifra: 50333

Kategorija proizvoda: Matične ploče

Proizvođač: GIGABYTE

Cena: 29.263 rsd.



Support for 12th Generation Intel® Core™, Pentium® Gold and Celeron® Processors*
Memory
L3 cache varies with CPU
Support for
* Please refer to "CPU Support List" for more information.
DDR5 6000(O.C.) / 5800(O.C.) / 5600(O.C.) / 5400(O.C.) / 5200(O.C.) / 4800/4000 MHz memory modules
4 x DDR DIMM sockets supporting up to 128 GB (32 GB single DIMM capacity) of system memory
Dual channel memory architecture
Support for ECC Un-buffered DIMM 1Rx8/2Rx8 memory modules (operate in non-ECC mode)
Support for non-ECC Un-buffered DIMM 1Rx8/2Rx8/1Rx16 memory modules
Support for Extreme Memory Profile (XMP) memory modules
(Please refer "Memory Support List" for more information.)

Audio

Realtek® ALC1220-VB CODEC
* The back panel line out jack supports DSD audio.
High Definition Audio
2/4/5.1/7.1-channel
Support for S/PDIF Out

Wireless Communication module

WIFI Module

WIFI a, b, g, n, ac, ax, supporting 2.4/5 GHz
Dual-Band
BLUETOOTH 5.2
Support for 11ax 160MHz wireless standard and up to 2.4 Gbps data rate

Chipset

Intel® B660 Express Chipset

Onboard Graphics

Integrated Graphics Processor-Intel® HD Graphics support:

1 x DisplayPort, supporting a maximum resolution of 4096x2304@60 Hz
* Support for DisplayPort 1.2 version and HDCP 2.3
1 x HDMI port, supporting a maximum resolution of 4096x2160@60 Hz
* Support for HDMI 2.1 version and HDCP 2.3.
** Support native HDMI 2.1 TMDS compatible ports

(Graphics specifications may vary depending on CPU support.)

LAN

Intel® 2.5GbE LAN chip
Expansion Slots
1 x PCI Express x16 slot, running at x16 (PCIEX16) (The PCIEX16 slot conforms to PCI Express 4.0 standard.)

1 x PCI Express x16 slot, running at x4 (PCIEX4)
* The PCIEX4 slot shares bandwidth with the M2M_SB connector. The PCIEX4 slot becomes unavailable when a device is installed in the M2M_SB connector.

1 x PCI Express x16 slot,