



Firma: G Store & Repair doo
Adresa: Bul.Mihajla Pupina 10z/3
Telefon: 011 785 66 66
Fax:
PIB: 112029009
E-mail: office@gstore.rs

MB s1700 Gigabyte B660 GAMING X AX

Šifra: 50334

Kategorija proizvoda: Matične ploče

Proizvođač: GIGABYTE

Cena: 25.047 rsd.



for 12th Generation Intel
® Core™, Pentium® Gold
and Celeron®
Processors*
Support for DDR4
L3 cache varies with CPU
4400(O.C.) /
* Please refer to "CPU Support List" for more
4300(O.C.) / 4266(O.C.) /
information
4133(O.C.) / 4000(O.C.) /
3866(O.C.) / 3800(O.C.) /
3733(O.C.) / 3666(O.C.) /
3600(O.C.) / 3466(O.C.) /
3400(O.C.) / 3333(O.C.) /
3300(O.C.)

/3200/3000/2933/2666/2400/2133

MHz memory modules

4 x DDR DIMM sockets
supporting up to 128 GB
(32 GB single DIMM
capacity) of system
memory

Dual channel memory
architecture

Support for ECC Un-
buffered DIMM

1Rx8/2Rx8 memory
modules (operate in non-
ECC mode)

Support for non-ECC Un-
buffered DIMM

1Rx8/2Rx8/1Rx16
memory modules

Support for Extreme
Memory Profile (XMP)
memory modules

(Please refer "Memory Support List" for more
information.)

Audio

Realtek® Audio CODEC

High Definition Audio

2/4/5.1/7.1-channel

Support for S/PDIF Out

Wireless Communication module

AMD Wi-Fi 6E RZ608 (MT7921K)

WIFI a, b, g, n, ac, ax,
supporting 2.4/5/6 GHz
carrier frequency bands

BLUETOOTH 5.2

Support for 11ax 80MHz

Chipset

Intel® B660 Express

Chipset

Onboard Graphics

Integrated Graphics Processor-Intel® HD Graphics
support:

1 x DisplayPort,
supporting a maximum
resolution of

4096x2304@60 Hz

* Support for DisplayPort

1.2 version and HDCP 2.3

1 x HDMI port,

supporting a maximum
resolution of

4096x2160@60 Hz

* Support for HDMI 2.1

version and HDCP 2.3.

** Support native HDMI

2.1 TMDS compatible

ports.

(Graphics specifications may vary depending on CPU
support.)

LAN

Realtek® 2.5GbE LAN

Expansion Slots

1 x PCI Express x16 slot,
running at x16 (PCIEX16)

* For optimum
performance, if only one
PCI Express graphics
card is to be installed, be
sure to install it in the
PCIEX16 slot.

(The PCIEX16 slot
conforms to PCI Express
4.0 standard.)

2 x PCI Express x16 slots,
running at x1 (PCIEX1_1,