



Firma: G Store & Repair doo  
Adresa: Bul.Mihajla Pupina 10z/3  
Telefon: 011 785 66 66  
Fax:  
PIB: 112029009  
E-mail: [office@gstore.rs](mailto:office@gstore.rs)

---

# Matična ploča AM4 ASUS PRIME X570-P HDMI/M.2

Šifra: 53005

Kategorija proizvoda: Matične ploče

Proizvođač: ASUS



**Cena: 18.638 rsd.**

<b>Tip procesora</b>	AMD
<b>Podnožje</b>	AMD® AM4
<b>Čipset</b>	AMD® X570
<b>Format ploče</b>	ATX
<b>Podržani procesori</b>	AMD AM4 Socket 3rd and 2nd AMD Ryzen™ /2nd and 1st Gen AMD Ryzen™ with Radeon™ Vega
<b>Podržana memorija</b>	DDR4
<b>Memorija</b>	<b>3rd Gen AMD Ryzen™ Processors</b> 4 x DIMM, Max. 128GB, DDR4 4400(O.C.)/4266(O.C.)/4133(O.C.)/4000(O.C.)/3866(O.C.)/3733(O.C.)/3600(O.C.)/3466(O.C.)/3400 MHz Un-buffered Memory <b>2nd Gen AMD Ryzen™ Processors</b> 4 x DIMM, Max. 128GB, DDR4 3600(O.C.)/3466(O.C.)/3400(O.C.)/3200(O.C.)/3000(O.C.)/2933/2800 <b>2nd and 1st Gen AMD Ryzen™ with Radeon™ Vega Graphics Processors</b> 4 x DIMM, Max. 128GB, DDR4 3200(O.C.)/3000(O.C.)/2933/2800/2666/2400/2133 MHz Memory Dual Channel Memory Architecture ECC Memory (ECC mode) support varies by CPU.
<b>Multi-GPU podrška</b>	<b>3rd and 2nd Gen AMD Ryzen™ /2nd and 1st Gen AMD Ryzen™ with Radeon™ Vega Graphics Processors</b> Supports AMD 2-Way CrossFireX™ Technology
<b>Integrirana grafička karta</b>	Integrated Graphics in the 2nd and 1st Gen AMD Ryzen™ with Radeon™ Vega Graphics Processors VGA output support : HDMI port - Supports HDMI 1.4b with max. resolution 4096 x 2160 @ 24 Hz
<b>Slotovi za proširenje</b>	<b>3rd Gen AMD Ryzen™ Processors</b> 1 x PCIe 4.0 x16 (x16 mode) <b>2nd Gen AMD Ryzen™ Processors</b> 1 x PCIe 3.0 x16 (x16 mode) <b>2nd and 1st Gen AMD Ryzen™ with Radeon™ Vega Graphics Processors</b> 1 x PCIe 3.0 x16 (x8 mode) <b>AMD X570 chipset</b> 1 x PCIe 4.0 x16 (max at x4 mode) 3 x PCIe 4.0 x1

<b>Storage</b>	<p><b>3rd Gen AMD Ryzen™ Processors :</b> 1 x M.2_1 socket 3, with M Key, Type 2242/2260/2280 (PCIe 4.0 x4 and SATA modes) storage device</p> <p><b>2nd Gen AMD Ryzen™ /2nd and 1st Gen AMD Ryzen™ with Radeon™ Vega Graphics Processors :</b> 1 x M.2_1 socket 3, with M Key, Type 2242/2260/2280 (PCIe 3.0 x4 and SATA modes) storage device</p> <p><b>AMD X570 chipset :</b> 1 x M.2_2 socket 3, with M Key, Type 2242/2260/2280/22110(PCIe 4.0 x4 and SATA modes) storage device</p> <p>6 x SATA 6Gb/s port(s) Support Raid 0, 1, 10</p>
<b>Mrežna karta</b>	<p>Realtek® RTL8111H ASUS LAN Guard</p>
<b>Zvučna karta</b>	<p>Realtek® S1200A 8-Channel High Definition Audio CODEC *</p> <ul style="list-style-type: none"> <li>- Supports : Jack-detection, Front Panel Jack-retasking</li> <li>- Front panel audio connector (AAFP)</li> </ul>
<b>USB</b>	<p><b>3rd and 2nd Gen AMD Ryzen™ /2nd and 1st Gen AMD Ryzen™ with Radeon™ Vega Graphics Processors :</b> 2 x USB 3.2 Gen 2 port(s) (2 at back panel, teal blue, Type-A *)</p> <p><b>3rd and 2nd Gen AMD Ryzen™ /2nd and 1st Gen AMD Ryzen™ with Radeon™ Vega Graphics Processors :</b> 2 x USB 3.2 Gen 1 port(s) (2 at back panel, blue, Type-A)</p> <p><b>AMD X570 chipset :</b> 2 x USB 3.2 Gen 2 port(s) (2 at back panel, teal blue, Type-A)</p> <p><b>AMD X570 chipset :</b> 4 x USB 3.2 Gen 1 port(s) (4 at mid-board)</p> <p><b>AMD X570 chipset :</b> 5 x USB 2.0 port(s) (2 at back panel, , 3 at mid-board)</p> <p>* The USB ports under the LAN port can run at USB 3.2 Gen 2 speeds with 3rd Gen AMD Ryzen™</p>
<b>Konektori na zadnjoj strani</b>	<p>1 x PS/2 keyboard/mouse combo port(s) 1 x HDMI 1 x LAN (RJ45) port(s) 2 x USB 2.0 3 x Audio jack(s) 2 x USB 3.2 Gen 1 (up to 5Gbps) ports Type-A 4 x USB 3.2 Gen 2 (up to 10Gbps) ports (Type-A *)</p> <p>* The USB ports under the LAN port can run at USB 3.2 Gen 2 speeds with 3rd Gen AMD Ryzen™</p>
<b>Interni konektori</b>	<p>2 x Aura RGB Strip Headers 1 x Addressable Gen 2 header(s) 2 x USB 2.0 connector(s) support(s) additional 5 USB 2.0 port(s) 1 x M.2 Socket 3 with M Key, type 2242/2260/2280/22110 storage devices support (SATA mode &amp; X4 PCIe) 1 x M.2 Socket 3 with M Key, type 2242/2260/2280 storage devices support (SATA mode &amp; X4 PCIe) 1 x SPI TPM header 1 x COM port(s) connector(s) 6 x SATA 6Gb/s connector(s) 1 x CPU Fan connector(s) (1 x 4 -pin) 3 x Chassis Fan connector(s) (3 x 4 -pin) 1 x PCH_FAN (1 x 4 -pin) 1 x AIO_PUMP connector (1 x 4 -pin) 1 x S/PDIF out header(s) 1 x 24-pin EATX Power connector(s) 1 x 8-pin ATX 12V Power connector(s) 1 x 4-pin ATX 12V Power connector(s) 1 x Front panel audio connector(s) (AAFP) 1 x System panel(s) 1 x Chassis G-MISC i/o connector(s)</p>