

Cudy FS1016D 16-Port 10/100M Base-TX Port Switch, (Alt.Tenda S16)

Šifra: 53119

Kategorija proizvoda: Switch uređaji

Proizvođač: CUDY

Cena: 3.385,00 rsd.

- 16 x 10/100Mbps Auto-Negotiation RJ45 ports supporting Auto-MDI/MDIX
- Comply with IEEE 802.3, IEEE 802.3u, IEEE802.3x standards
- Supports MAC address auto-learning and auto-aging
- Supports IEEE802.3x flow control for Full-duplex Mode and backpressure for Half-duplex Mode
- Plug & Play, Desktop design

Plug and play, hassle-free, no configuring is required.

Auto MDI/MDIX eliminates the need for crossover cables.

Auto-negotiation on each port detects the link speed of a network device (10/100Mbps) and intelligently adjusts for compatibility and optimal performance.

High Performance

Auto-negotiation RJ-45 ports can provide large file transferring and also be compatible with any 10/100Mbps Ethernet devices. Featuring non-blocking switching architecture, the product forwards and filters packets at full wire-speed for maximum throughput.

IEEE 802.3x flow control for Full Duplex mode and backpressure for Half Duplex mode offer increased bandwidth to alleviate network congestion, making the switch work reliably.

10/100Mbps Ports for Faster Speed

Increase the speed of your network with the 16-port switch. Non-blocking, 16 10/100Mbps ports enables instant transferring of large, bandwidth intensive files without interference.

Smooth Online Experience

The switch connects up to 16 devices with a speed of up to 100Mbps (Half Duplex)/200Mbps (Full Duplex). Provides you with an extremely smooth experience to enjoy a powerful, seamless, affordable and easy-to-use network, ideal for multimedia, graphics, HD video and other applications that require large transfer allocation.

Energy Efficient and Power Saving

Automatically adjusts Power consumption according to the link status and cable length. This Gigabit Desktop Switch features the innovative energy-efficient technologies that can greatly expand your network capacity with much less power.

Standards: IEEE 802.3, IEEE 802.3u, IEEE 802.3x

Protocol: CSMA/CD

Data Rate: Ethernet: 10Mbps (Half Duplex)/20Mbps (Full Duplex) Fast Ethernet: 100Mbps (Half Duplex)/200Mbps (Full Duplex)

Transmission Method: Store-and-Forward

Switching Features: MAC address auto-learning and auto-aging Half and Full Duplex 1.6Gbps backplane bandwidth

Interfaces: 16 x 10/100Base-TX Port

LED Indicators: LAN~LAN16, Power

Cudy FS1016D 16-Port 10/100M Base-TX Port Switch,

MAC Address Table: 2K entries per device

Power Supply: DC 5V 1A

Dimensions W*D*H: 138mm x 103mm x 35 mm

Weight: 0.228kg

Operating Temperatur: 0°C~40°C (32°F~104°F)

Storage Temperature: -40°C~70°C (-40°F~158°F)

Relative Humidity: 10%~90%, non-condensing

Storage Humidity: 5%~95%, non-condensing

Package Contents: 1 x Power Adapter;1 x Switch;1 x User Manual