



Firma: G Store & Repair doo
Adresa: Bul.Mihajla Pupina 10z/3
Telefon: 011 785 66 66
Fax:
PIB: 112029009
E-mail: office@gstore.rs

MB s1700 Biostar B660GTA 4xDDR4M.2HDMI DP

Šifra: 55614

Kategorija proizvoda: Matične ploče

Proizvođač: BIOSTAR

Cena: 12.421 rsd.



Chipset	Intel B660
CPU SUPPORT	Support for 12th/ 13th Generation Intel Core™ i9/ i7/ i5/ i3 processors and Intel Pentium processors/ Intel Celeron processors in the LGA1700 package * Please refer to www.biostar.com.tw for CPU support list.
MEMORY	Supports Dual Channel DDR4-1866/ 2133/ 2400/ 2666/2800/2933/3200/3600(OC)/3800(OC)/4000(OC)/ 4133(OC)/4300(OC)/5000+(OC) 4 x DDR4 DIMM Memory Slot, Max. Supports up to 128 GB Memory Each DIMM supports non-ECC 4/ 8/ 16/ 32GB DDR4 module Support Intel Extreme Memory Profile (XMP) memory modules * Please refer to www.biostar.com.tw for Memory support list.
INTEGRATED VIDEO	By CPU model Supports DX12 Supports HDCP
STORAGE	-- Total supports 3 x M.2 socket and 8 x SATA III (6Gb/s) ports 8 x SATA III Connectors (6Gb/s) : Supports AHCI, RAID 0, 1, 5, 10 & Intel Rapid Storage Technology (Only SATA1~SATA4) 1 x M.2 (M Key) Socket (M2-PCIE4_64G_1) Supports M.2 Type 2280 SSD module Supports PCI-E 4.0 x 4 (64Gb/s) 1 x M.2 (M Key) Socket (M2_PCIE4_64G_2): Supports M.2 Type 2280 SSD module Supports PCI-E 4.0 x 4 (64Gb/s) Supports Intel Rapid Storage Technology and Intel Optane Technology 1 x M.2 (M Key) Socket (M2_PCIEG3_32G_SATA_1): Supports M.2 Type 2242/ 2260/ 2280/ 22110 SSD module Supports PCI-E 3.0 x4 (32Gb/s) & SATA III (6Gb/s)SSD Supports Intel Rapid Storage Technology and Intel Optane Technology * When using SATA SSD module on M.2 slot(M2_PCIEG3_32G_SATA_1), the SATA_8 connector will be disabled. ** When using PCIE SSD module on M.2 slot (M2_PCIEG4_64G_2), the PCIEG4X4 slot will be disabled.
LAN	Realtek RTL8125B 10/ 100/ 1000/ 2500 Mb/s auto negotiation, Half / Full duplex capability
AUDIO CODEC	ALC1220 7.1 Channels, High Definition Audio, Hi-Fi(Front)

USB	<p>2 x USB 3.2 (Gen2) Type-C ports (1 on rear I/O and 1 via internal header)</p> <p>5 x USB 3.2 (Gen2) ports (5 on rear I/Os)</p> <p>2 x USB 3.2 (Gen1) ports (2 via internal header)</p> <p>6 x USB 2.0 ports (2 on rear I/Os and 4 via internal header)</p>
EXPANSION SLOT	<p>2 x PCIe 3.0 x1 Slots</p> <p>1 x PCIe 5.0 x16 Slot (x16 mode)</p> <p>1 x PCIe 4.0 x16 Slot (x4 mode)</p>
REAR I/O	<p>2 x WIFI Antenna Ports</p> <p>1 x PS/2 Keyboard/ Mouse Port</p> <p>1 x HDMI Port (HDMI2.0)</p> <p>1 x DP Port</p> <p>1 x DVI-D Port</p> <p>1 x USB 3.2 (Gen2) Type-C Ports</p> <p>5 x USB 3.2 (Gen2) Ports</p> <p>2 x USB 2.0 ports</p> <p>1 x LAN port</p> <p>3 x Audio Jack</p>
INTERNAL I/O	<p>8 x SATA III Connectors (6Gb/s)</p> <p>1 x M.2 (E Key) Socket : Supports 2230 type Wi-Fi & Bluetooth module and Intel CNVi</p> <p>2 x USB 2.0 Headers (each header supports 2 USB 2.0 ports)</p> <p>1 x USB 3.2 (Gen1) Header (each header supports 2 USB 3.2 (Gen1) ports)</p> <p>1 x USB 3.2 (Gen2) Type C Header.</p> <p>1 x 4-Pin Power Connector</p> <p>1 x 8-Pin Power Connector</p> <p>1 x 24-Pin Power Connector</p> <p>1 x CPU Fan Connector</p> <p>1 x CPU water cooling connector (CPU_OPT)</p> <p>3 x System Fan Connectors</p> <p>1 x Front Panel Header</p> <p>1 x Front Audio Header</p> <p>1 x Internal Stereo Speaker Header</p> <p>1 x Clear CMOS Header</p> <p>1 x COM Port Header</p> <p>1 x TPM Header</p> <p>1 x Thunderbolt Header</p> <p>2 x LED Headers (5V)</p> <p>1 x LED Header (12V)</p> <p>1 x IO LED Header</p> <p>1 x SB LED Header</p> <p>* M.2 (E key) Wi-Fi card is not provided</p>
H/W MONITORING	<p>CPU / System Temperature Monitoring</p> <p>CPU / System Fan Monitoring</p> <p>Smart / Manual CPU Fan Control</p> <p>System Voltage Monitoring</p>
DIMENSION	ATX Form Factor Dimension: 30.5 cm x 24.4cm (W x L)
OS SUPPORT	<p>Supports Windows 10(64bit) / 11(64bit)</p> <p>?Biostar reserves the right to add or remove support for any OS with or without notice.</p>
BUNDLE SOFTWARE	<p>Racing GT Utility</p> <p>BullGuard</p>