



Firma: G Store & Repair doo  
Adresa: Bul.Mihajla Pupina 10z/3  
Telefon: 011 785 66 66  
Fax:  
PIB: 112029009  
E-mail: office@gstore.rs

---

Matična ploča 1200 Asus PRIME B460-PLUS  
VGA/HDMI/DVI/M.2

---



Šifra: 58361

Kategorija proizvoda: Matične ploče

Proizvođač: ASUS

**Cena: 17.224 rsd.**

Tip procesora:	Intel
Podnožje:	Intel® 1200
Čipset:	Intel® B460
Format ploče:	ATX Intel Socket 1200 10-e generacije, Intel Core, Pentium Gold i Celeron procesori - Podržava Intel procesore sa litografijom do 14 nm - Podržava Intel Turbo Boost 2.0 i Intel Turbo Boost Max 3.0 tehnologije
Podržani procesori:	
Podržana memorija:	DDR4 DIMM, Max. 128GB, DDR4 2933/2800/2666/2400/2133 MHz Non-ECC, Un-buffered Memory - Dual Channel memorijska arhitektura - Podržava Intel Extreme Memory Profile (XMP)
Memorija:	
Multi-GPU podrška:	- Podržava AMD 2-Way CrossFireX tehnologiju
Integrirana grafička karta:	1 x D-Sub 1 x HDMI 1.4b 1 x DVI-D 1.4 Intel 10th Gen Processors - 1 x PCIe 3.0/2.0 x16 (x16 mode) Intel B460 Chipset - 1 x PCIe 3.0/2.0 x16 (x4 mode) - 2 x PCIe 3.0/2.0 x1 - 2 x PCI
Slotovi za proširenje:	- Ukupna podrška: 2 x M.2 slota i 6 x SATA 6Gbps portova Intel B460 Chipset: - 1 x M.2 Socket 3, with M key, type 2242/2260/2280 storage devices support (SATA & PCIE mode) - 1 x M.2 Socket 3, with M key, type 2242/2260/2280/22110 storage devices support (PCIE 3.0 x 4 mode) - 6 x SATA 6Gbps port(s) - Raid 0, 1, 5, 10 - Intel Rapid Storage tehnologija - Intel Optane Memory Ready
Storage:	
Mrežna karta:	Realtek RTL8111H, 1 x Gigabit LAN Controller(s), LANGuard Realtek ALC887 7.1-Channel High Definition Audio CODEC - Podržava: Jack-detection, do 24-
Zvučna karta:	Bit 192kHz playback Nazad USB Port ( Total 6 ) - 4 x USB 3.2 Gen 1 (up to 5Gbps) port(s) (4 x Type-A) - 2 x USB 2.0 port(s) (2 x Type-A) Napred USB Port ( Total 6 ) - 2 x USB 3.2 Gen 1 (up to 5Gbps) port(s) - 4 x USB 2.0 port(s)
USB:	
Konektori na zadnjoj strani:	1 x PS2 keyboard/mouse combo port(s) 1 x DVI-D 1 x D-Sub 1 x 1 x CPU Fan connector(s) (1 x 4 - pin) 1 x LAN (RJ45) port(s) 4 x 3 x Chassis Fan connector(s) USB 3.2 Gen 1 Type-A 2 x USB (3 x 4 - pin) 1 x AAFP connector 2 2.0 3 x Audio jack(s) 1 x Lighting Control RGB Strip