



Firma: G Store & Repair doo
Adresa: Bul.Mihajla Pupina 10z/3
Telefon: 011 785 66 66
Fax:
PIB: 112029009
E-mail: office@gstore.rs

Matična ploča 1200 Biostar H510MHE 2.0
HDMIVGAM.2



Šifra: 59044

Kategorija proizvoda: Matične ploče

Proizvođač: BIOSTAR

Cena: 8.778 rsd.

Tip procesora:	Intel
Podnožje:	Intel®; 1200
Čipset:	Intel H510
Format ploče:	Micro ATX Support for 10th 11th Generation Intel Core i9 i7 i5 i3 processors and Intel Pentium processors Intel Celeron processors in the LGA1200 package
Podržani procesori:	
Podržana memorija:	DDR4 Supports Dual Channel DDR4 3200 2933 2666 2400 2133 1866 2 x DDR4 DIMM Memory Slot, Max. Supports up to 64 GB Memory Each DIMM supports non-ECC 481632GB DDR4 module
Memorija:	
Integrirana grafička karta:	By CPU model Supports DX12 Supports HDCP Supports HDMI 1.4 version 1 x PCIe 3.0 x1 Slot 1 x PCIe 3.0 4.0 x16 Slot (x16 mode) * The PCIe 4.0 only depends on Rocket Lake CPUs.
Slotovi za proširenje:	-- Total supports 1 x M.2 socket and 4 x SATA III (6Gbs) ports 4 x SATA III Connectors (6Gbs) 1 x M.2 (M Key) Socket: Supports M.2 Type 2242 2260 2280 SSD module. Supports PCIe 3.0 x4 (32Gbs) - NVMe AHCI SSD & SATA III (6Gbs) SSD
Storage:	
Mrežna karta:	Intel I219V 10 100 1000 Mbs auto negotiation, Half Full duplex capability
Zvučna karta:	ALC897 7.1 Channels, High Definition Audio
USB:	4 x USB 3.2(Gen1) ports (2 on rear IOs and 2 via internal headers) 8 x USB 2.0 ports (4 on rear IOs and 4 via internal headers)
Konektori na zadnjoj strani:	2 x WIFI Antenna Ports 1 x PS2 Keyboard Mouse 1 x HDMI Port 1 x VGA Port 2 x USB 3.2 (Gen1) Ports 4 x USB 2.0 ports (4 on rear IOs and 4 via internal headers) 1 x M.2 (E Key) Socket : Supports 2230 type Wi-Fi & Bluetooth module and Intel CNVi 2 x USB 2.0 Header (each header supports 2 USB 2.0 ports) 1 x USB 3.2 (Gen1) Header (each header supports 2 USB 3.2 (Gen1) ports) 1 x 8-Pin Power Connector 1 x 24-Pin Power Connector 1 x CPU Fan Connector 1 x System Fan Connector 1 x Front Panel Header 1 x Front Audio Header 1 x Internal Stereo Speaker Header 1 x Clear CMOS Header 1 x COM