



Firma: G Store & Repair doo  
Adresa: Bul.Mihajla Pupina 10z/3  
Telefon: 011 785 66 66  
Fax:  
PIB: 112029009  
E-mail: [office@gstore.rs](mailto:office@gstore.rs)

---

Matična ploča AM4 Biostar X570GT VGA/HDMI/M.2

---

Šifra: 59543

Kategorija proizvoda: Matične ploče

Proizvođač: BIOSTAR



**STORE**  
UBODI PRAVO MESTO ZA TEHNIKU

**Cena: 16.835 rsd.**

Tip procesora:	AMD
Podnožje:	AMD&reg; AM4
Čipset:	AMD&reg; X470
Format ploče:	Micro-ATX Socket AM4 supports 3rd and 2nd Gen AMD Ryzen 3rd and 2nd Gen AMD Ryzen with Radeon Vega Graphics processors. Maximum CPU TDP (Thermal Design Power):
Podržani procesori:	105Watt
Podržana memorija:	Supports Dual Channel DDR4 DDR4 1866 2133 2400 2667 Supports Dual Channel DDR4 2933(OC) 3200(OC) 3600(OC) 4000+(OC) 4 x DDR4 DIMM Memory Slot, Max. Supports up to 128 GB Memory Each DIMM supports non-ECC and ECC Un-buffered 8 16 32 GB DDR4 module * DDR4 - 2667 only for Ryzen CPU.
Memorija:	
Integrisana grafička karta:	By CPU model Supports DX12, 2x PCIe 3.0 x1 Slot 1x PCIe 4.0 Supports HDCP x16 Slot (PEX16_1) * Note : Supports x16 lanes with AMD Ryzen 2nd and 3rd Gen processors. Supports x8 lanes with AMD Ryzen with Radeon Vega Graphics processors. * According to different CPUs will have different speeds. * Note: PCIe 4.0 speed only for AMD Ryzen 3rd Gen Matisse.
Slotovi za proširenje:	
Storage:	4x SATA III Connector (6Gbs): Supports RAID 0, 1, 10 1x M.2 (Key M) Slot (PCIE-M2) : Supports M.2 Type 2242 2260 2280 SSD module Supports SATA III (6.0Gbs) SSD Supports PCI-E Gen4 x4 (64Gbs) speed, which depends only on Ryzen 3rd Gen Matisse.
Mrežna karta:	RTL8111H 10 100 1000 Mbs auto negotiation, Half Full duplex capability Support Super LAN Surge Protection
Zvučna karta:	ALC887 7.1 Channels, High Definition Audio, Hi-Fi(Front) 6x USB 3.1 Gen1 (5Gbs) port (4 on rear IOs and 2 via internal headers) 6x USB 2.0 port (2 on rear IOs and 4 via internal headers)
USB:	
Konektori na zadnjoj strani:	1x PS2 Keyboard Port 1x HDMI Port 1x VGA Port 1x LAN port 4x SATA III (6.0Gbs) Connector 2x USB 2.0 Header (each header supports 2 USB 2.0 ports) 1x USB