



Firma: G Store & Repair doo

Adresa: Bul.Mihajla Pupina 10z/3

Telefon: 011 785 66 66

Fax:

PIB: 112029009

E-mail: office@gstore.rs

Matična ploča 1200 Biostar B460GTQ
HDMIDVIDPM.2



Šifra: 60236
Kategorija proizvoda: Matične ploče
Proizvođač: INTEL

Cena: 12.294 rsd.

Tip procesora:	Intel
Podnožje:	Intel®; 1200
Čipset:	Intel®; B460
Format ploče:	Socket ATX Socket ATX for 10th Gen Intel Core™, Pentium and Celeron processors * 10th Generation Intel Core™ Processor Family only support 400-Series. * Please refer to www.biostar.com.tw for CPU support list.
Podržani procesori:	
Podržana memorija:	Supports Dual Channel DDR4 DDR4 2133 2400 2666 2800 2933 4 x DDR4 DIMM Memory Slot, Max. Supports up to 128 GB Memory Each DIMM supports non-ECC 481632GB DDR4 module * Please refer to Memory Support List for more information. Core (i9i7) support DDR4 up to 2933 MHz; Core (i5i3), Pentium and Celeron support DDR4 up to 2666 MHz.
Memorija:	
Integrirana grafička karta:	By CPU model Supports DX 12 Supports HDCP
Slotovi za proširenje:	6 x SATA III Connectors (6Gbs) 1 x PCIe 3.0 x16 Slot (PCIe 3.0 x16) 2 x M.2 (M Key) Socket (PCIe-M2_1): Supports M.2 Type 2242 2260 2280 SSD module Supports PCIe 3.0 x 4 (32Gbs) - NVMe AHCI SSD & SATA III (6Gbs) SSD 1 x M.2 (M Key) Socket (PCIe-M2_2): Supports M.2 Type 2242 2260 2280 SSD module Supports PCIe 3.0 x 4 (32Gbs) - NVMe AHCI SSD Supports Intel Optane Technology
Storage:	* When using SATA SSD module on PCIe-M2_1 slot, the SATA_3U connector will be disabled.
Mrežna karta:	Intel i219V 10 100 1000 Mbs auto negotiation, Half Full duplex capability Supports Super LAN Surge Protection
Zvučna karta:	ALC1150 7.1 Channels, High Definition Audio, Hi-Fi(Front) 6 x USB 3.2(Gen1) ports (4 on rear IOs and 2 via internal headers) 6 x USB 2.0 ports (2 on rear IOs and 4 via internal headers)
USB:	
Konektori na zadnjoj strani:	1 x PS2 Keyboard 1 x PS2 Mouse 1 x DP Port 1 x HDMI Port 1 x DVI-D Port 4 x USB 3.2 (Gen1) Ports 2 x USB 2.0 Ports 1 x LAN (RJ45) 2 x SATA III Connectors (6Gbs) 2 x USB 2.0 Header (each header supports 2 USB 2.0 ports) 1 x USB 3.2 (Gen1) Header (each header