



Firma: G Store & Repair doo  
Adresa: Bul.Mihajla Pupina 10z/3  
Telefon: 011 785 66 66  
Fax:  
PIB: 112029009  
E-mail: [office@gstore.rs](mailto:office@gstore.rs)

---

Matična ploča Asus Prime J4005I-C  
VGAHDMIRS232M.2

---



Šifra: 60290

Kategorija proizvoda: Matične ploče

Proizvođač: ASUS

**Cena: 8.923 rsd.**

Tip procesora:	Intel
Format ploče:	Mini ITX Integrisan Intel® Celeron® J4005 Processor 2.00 GHz (4MB keš memorije, do 2.70 GHz)
Podržani procesori:	
Podržana memorija:	DDR4 2 x U-DIMM, Max. 8GB, DDR4 24002133 MHz Non-ECC, Un- buffered Memory Dvo-kanalna memorijska arhitektura
Memorija:	Multi-VGA izlaz : HDMIRGBLVDS port - Podržava HDMI sa maksimalnom rezolucijom 4096 x 2304 @ 24 Hz - Podržava LVDS sa maksimalnom rezolucijom 1920 x 1200 @ 60 Hz - Podržava RGB sa maksimalnom rezolucijom 1920 x 1200 @ 60 Hz Maksimalna deljena memorija 512 MB (za iGPU isključivo) Podržava do 3 displeja istovremeno
Integrisana grafička karta:	
Storage:	1 x M.2 Socket 3, , with M Key, type 22602280 storage devices support (PCIe mode) 2 x SATA 6Gbs port(s)
Mrežna karta:	Realtek® RTL8111H, 1 x Gigabit LAN Controller(s) Realtek® ALC887-VD2 8-Channel High Definition Audio CODEC - Podržava : Jack-detection, Front Panel Jack-retasking
Zvučna karta:	Built-in Controller : 4 x USB 3.1 Gen 1 porta (2 na zadnjem panelu , 2 preko internih konektora) Built-in Controller : 2 x USB 2.0 porta (2 na zadnjem panelu) GL852G USB Hub : 4 x USB porta (4 preko internih konektora)
USB:	
Konektori na zadnjoj strani:	1 x PS2 keyboard (purple) 1 x PS2 mouse 1 x USB 3.1 (Type-C) 1 x USB 3.1 (Type-A) 1 x USB 2.0 (Type-A) 1 x HDMI 1 x LAN (RJ45) (optional) 2 x USB 3.1 Gen 1 port (USB 2.0 USB COM port(s) 3 x Audio jack(s) additional 2 USB 2.0 port(s) 1 x M.2 Socket 1 with E Key, type 2230 WiFiBT devices support or PCIeUSB mode 1 x M.2 Socket 3 with M key, type 22602280 storage devices support (PCIe x 2 mode) 1 x LPT header 1 x COM port(s) connector(s) 2 x SATA 6Gbs connector(s) 1 x Chassis Fan connector(s) (1 x 4 -pin) 1 x SPDIF out header(s) 1 x 24-pin EATX Power connector(s) 1 x 4- pin ATX 12V Power connector(s) 1 x Front panel audio connector(s) (AAFP) 1 x Chassis Intrusion