



Firma: G Store & Repair doo  
Adresa: Bul.Mihajla Pupina 10z/3  
Telefon: 011 785 66 66  
Fax:  
PIB: 112029009  
E-mail: office@gstore.rs

---





MB s1700 GIGABYTE B660M GAMING AC DDR4

Šifra: 62856

Kategorija proizvoda: Matične ploče

Proizvođač: GIGABYTE

**Cena: 15.728 rsd.**



**Specifikacija:** Proizvodjac GIGABYTE EAN 4719331830434 CPU LGA1700 socket: Support for 13th Generation Intel® Core™ Processors and 12th Generation Intel® Core™, Pentium® Gold and Celeron® Processors\* L3 cache varies with CPU \* Please refer to "CPU Support List" for more information. Chipset Intel® B660 Express Chipset Memory Support for DDR4 5333(O.C.)/DDR4 5133(O.C.)/DDR4 5000(O.C.)/4933(O.C.)/4800(O.C.)/ 4700(O.C.)/4600(O.C.)/ 4500(O.C.)/ 4400(O.C.)/ 4300(O.C.)/4266(O.C.) / 4133(O.C.) / 4000(O.C.) / 3866(O.C.) / 3800(O.C.) / 3733(O.C.) / 3666(O.C.) / 3600(O.C.) / 3466(O.C.) / 3400(O.C.) / 3333(O.C.) / 3300(O.C.) / 3200/3000/2933/2666/2400/2133 MT/s memory modules 2 x DDR4 DIMM sockets supporting up to 64 GB (32 GB single DIMM capacity) of system memory Dual channel memory architecture Support for ECC Un-buffered DIMM 1Rx8/2Rx8 memory modules (operate in non-ECC mode) Support for non-ECC Un-buffered DIMM 1Rx8/2Rx8/1Rx16 memory modules Support for Extreme Memory Profile (XMP) memory modules (Please refer "Memory Support List" for more information.) Onboard Graphics Integrated Graphics Processor-Intel® HD Graphics support: 1 x D-Sub port, supporting a maximum resolution of 1920x1200@60 Hz 1 x HDMI port, supporting a maximum resolution of 4096x2160@60 Hz \* Support for HDMI 2.1 version and HDCP 2.3. \*\* Support native HDMI 2.1 TMDS compatible ports. 1 x DisplayPort, supporting a maximum resolution of 4096x2304@60 Hz \* Support for DisplayPort 1.2 version and HDCP 2.3 (Graphics specifications may vary depending on CPU support.) Support for up to 3 displays at the same time Audio Realtek® Audio CODEC High Definition Audio 2/4/5.1/7.1-channel \* To configure 7.1-channel audio, you need to open the audio software and select Device advanced settings > Playback Device to change the default setting first. LAN Realtek® 2.5GbE LAN chip (2.5 Gbps/1 Gbps/100 Mbps) Wireless Communication module Intel® Wi-Fi AC 3168 (PCB rev. 1.0) WIFI 802.11a/b/g/n/ac, supporting 2.4/5 GHz Dual-Band BLUETOOTH 4.2 Support for 11ac wireless standard and up to 433 Mbps data rate Intel® Wi-Fi AC 9560 (PCB rev. 1.1) WIFI a, b, g, n, ac, supporting 2.4/5 GHz Dual-Band BLUETOOTH 5.1 Support for 11ac 160MHz wireless standard and up to 1.73 Mbps data rate. \* Actual data rate may vary depending on environment and