



Firma: G Store & Repair doo  
Adresa: Bul.Mihajla Pupina 10z/3  
Telefon: 011 785 66 66  
Fax:  
PIB: 112029009  
E-mail: [office@gstore.rs](mailto:office@gstore.rs)

---

Matična ploča ASUS TUF GAMING B760-PLUS  
WIFI1700' ( 'TUF G B760-P WIFI' )

---

Šifra: 63692

Kategorija proizvoda: Matične ploče

Proizvođač: ASUS



**Cena: 25.724 rsd.**

		Addressable Gen 2 headers, Aura RGB Header, DIGI+VRM, ESD Guards, Moze heatsink, Mezo Latch, Overvoltage Protection, ProCool, Q-DIMM, Q-LED (CPU [red], DRAM [yellow], VGA [white], Boot Device [yellow green]), Q-Slot, SafeDIMM, SafeSlot Core+, Stainless-Steel Back IO, TUF LANGuard, VRM heatsink design
Audio	Napomena:	Dedicated audio PCB layers, Front Panel Jack-retasking, High Definition, Jack-detection, Multi-streaming, Premium audio capacitors, Supports up to 24-Bit/192 kHz playback
Fizičke karakteristike	Format: Dimenzije: Tip memorije: Fiksirajući otvori: Memorijski slotovi:	ATX 305mm x 244mm DDR4 2.133MHz, 2.400MHz, 2.666MHz, 2.800MHz, 2.933MHz, 3.000MHz, 3.200MHz, 3.300Mhz (O.C.), 3.400Mhz (O.C.), 3.466Mhz (O.C.), 3.600Mhz (O.C.), 3.733Mhz (O.C.), 4.000Mhz (O.C.), 4.266Mhz (O.C.), 4.400Mhz (O.C.), 4.600Mhz (O.C.), 4.800Mhz (O.C.), 5.000Mhz (O.C.), 5.0066Mhz (O.C.), 5.333Mhz (O.C.)
Memorija	Podržane memorije:	
Mreža	Žična mreža (LAN): Model: Wi-Fi:	1010010002500 Mbps (2.5GbE) Realtek® Da
Osnovne karakteristike	Procesorsko ležište (socket): Čipset: Grafika:	Intel 1700 Addressable Gen 2 headers, Aura RGB Header, DIGI+VRM, ESD Guards, Moze heatsink, Mezo Latch, Overvoltage Protection, ProCool, Q-DIMM, Q-LED (CPU [red], DRAM [yellow], VGA [white], Boot Device [yellow green]), Q-Slot, SafeDIMM, SafeSlot Core+, Stainless-Steel Back IO, TUF LANGuard, VRM heatsink design
Ostale karakteristike	Podržane tehnologije:	
Priključci na zadnjem panelu	DisplayPort priključci: HDMI priključci: Ukupno USB priključaka:	1x DisplayPort 1.4 1x HDMI 2.1 6
Reklamacioni period	Reklamacioni period: SATA priključci (ukupno):	36 meseci 4
Skladišni interfejs	SATA priključci: Ostali skladišni interfejs:	4x SATA III 3x M.2
Slotovi	PCI Express x16 slot: PCI Express x1 slot: PCI slot:	1x PCI Express 3.0 (x4 mode), 1x PCI Express 5.0 (x16 mode) 2x PCI Express 3.0 4