

Tenda O6 outdoor long range Point to Point CPE 5GHz

Tenda O6 outdoor long range Point to Point CPE
5GHz 11AC 433Mbps, 16dB, 10km

Šifra: 65586
Kategorija proizvoda: Ruteri
Proizvođač: TENDA

Cena: **11.675,00** rsd.

Dimension270*94.86*67.5mm
Frequency Range5GHz
Maximum wireless speed433Mbps
CPU ProcessorBroadcom 800MHz
GND Terminal1
Interface1*GE PoE/WAN/LAN port
Mode SwitchStation: The device only work in Station mode
Off: The device work on
AP/Station/Universal Repeater/WISP/Router mode
AP: The device only work in AP mode
ButtonReset: Press 10 seconds or more to restore to default settings
Bridge: Press 3 seconds and release it to bridge uplink AP
Antenna16dbi Directional Antenna
Antenna Beamwidth Horizontal: 30°
Vertical: 15°
Maximum Consumption9W
Lightning Protection6KV
Waterproof LevelIP64
LEDLAN,LED1,LED2,LED3
Power Supply24v 0.5A PoE Injector
Operating modeAP/Station/Universal Repeater/WISP/Router
Standard&ProtocolIEEE 802.11ac/n/a
Wireless SpeedEnable/Disable Wireless Radio
SSID Hidden
Wireless Client isolation
Sensitivity Threshold
WMM Capable
APSD Capable
Wireless Access Control
Wireless Client list
Wireless Security64/128 WEP,WPA-PSK,WPA2-PSK,WPA&WPA2-PSK,WPA,WPA2
Transmit PowerAdjustable power by 1dBm
Reception SensitivityMCS0: -90dbm
MCS7: -72dbm
DHCP ServerDHCP Server
Clients list
VPN Pass-throughPPTP,L2TP
Ping WatchdogSupport
Speed TestSupport
Remote Web accessSupport
Schedule RebootSupport
Page TimeoutSupport

Dyndnsnoip, dyndns.org
Network DiagnosesPing, Traceroute, Signal Scan
Management ToolTime&Date Setting
System Log
Firmware update
Backup/Restore Configuration
Username Managerment
TemperatureOperating Temperature:-20? ~ 55?
Storage Temperature:-40? ~ 70?
HumidityOperating Humidity:10%~90% non-condensing
Storage Humidity:10%~90% non-condensing
Default SettingsIP Address: 192.168.2.1
Login Username:admin
Login Password:admin
CertificationFCC/CE/RoHS