

Napajanje Thermaltake 550W Smart BM2 ModularPremium
 EditionPS-SPD-0550MNFABE-1

Šifra: 73957
 Kategorija proizvoda: Napajanja
 Proizvođač: Thermaltake



Cena: 8.792 rsd.

| | |
|-------------------------------|--|
| P/N | PS-SPD-0550MNFABU-1 |
| WATTS | 550W |
| RGB FAN | No |
| MODEL | SP-550AH3CCB-B SP-550AH3CLB-B |
| TYPE | ATX 12V v2.4 and EPS v2.92 |
| MAX. OUTPUT CAPACITY | 550W |
| COLOR | Black |
| DIMENSION (W / H / D) | 150mm(W) x 86mm(H) x 160mm(D) |
| PFC (POWER FACTOR CORRECTION) | Active PFC |
| POWER GOOD SIGNAL | 100-500 msec |
| HOLD UP TIME | > 12msec at 80% of full load at 230Vac input |
| INPUT CURRENT | 8A max. 5 - 10A |
| INPUT FREQUENCY RANGE | 47Hz -63Hz |
| INPUT VOLTAGE | 100V-240V~ |
| OPERATING TEMPERATURE | 0°C to +40°C +5°C to +40°C |
| OPERATING HUMIDITY | 20% to 90%,non-condensing 20% to 85%,non-cond |
| STORAGE TEMPERATURE | -20 °C to +70 °C -40 °C to +55 °C |
| STORAGE HUMIDITY | 5% to 95%, non-condensing 10% to 95%, non-cond |
| COOLING SYSTEM | 140mm Fan: 2300 R.P.M. ± 10% 140mm Fan: 1600 |
| EFFICIENCY | Meet 80 PLUS®Bronze at 115Vac input. |
| MTBF | 100,000 hrs minimum |
| SAFETY APPROVAL | cTUVus/TUV/CE/FCC/S-mark/EAC/BSMI/C-TICK/CCC |