

Supermicro MBD-X10DRD-I-O, Dual SKT, Intel C612 chipset, 10 x SATA3, 4 x PCI-E3.0, 2 x GbE, IPMI, E-ATX - Retail (X10DRD-I)

Supermicro MBD-X10DRD-I-O, Dual SKT, Intel C612 chipset, 10 x SATA3, 4 x PCI-E3.0, 2 x GbE, IPMI, E-ATX - Retail (X10DRD-I)

Šifra: 83781

Kategorija proizvoda: Dodatna oprema za server

Proizvođač: SUPERMIKRO

Cena: **52.023,00** rsd.

Chipset:	Intel C612
CPU Socket Standard:	Socket 2011
Supports Central Processor Unit:	Intel Xeon E5-2600v3 Series
Max. CPU Bus Clock Rate:	9.6 GTsec
Maximum Installable L3 Cache	45 MB
Memory Storage Capacity:	
CPU Maximum Quantity	2
Supports:	
Memory Type:	DDR4 SDRAM
Provides Error Checking Method:	ECC
Memory Speed:	2133MHz(PC4-17000) 1866MHz(PC4-14900) 1600MHz(PC4-12800)
Memory Form Factor:	DIMM 288-pin
Maximum Installable System	512 GB
Memory Storage Capacity:	
Memory Slot Total Quantity:	8
Memory Features:	Registered Load Reduced
Storage Controller Type:	SATA III
SATA Controller Interface Type:	Serial ATA III600
Supports RAID Level:	Level 0 Level 1 Level 10 Level 5
Video Controller Integrated:	yes
Video Chipset:	Aspeed AST2400
LAN Integrated:	yes
LAN Chipset:	Intel i350
Data Link Protocol Supports:	Gigabit EthernetFast EthernetEthernet
PCI Express 3.0 x8 Slot Quantity:	4
SATA III:	10
LAN:	2 (RJ-45)
USB2.0:	4 (4-pin USB (type A))
Serial:	1 (9-pin DB)
BIOS Type:	AMI
BIOS Features:	ACPI 1.0 Support ACPI 2.0 Support PCI 2.3

PnP Support
USB Keyboard support
ACPI 3.0 Support
128Mb EEPROM
ACPI 4.0 Support
SMBIOS 2.7.1 Support
UEFI 2.3.1

Maximum Operating Ambient 35 °C
Temperature:

Minimum Operating Ambient 10 °C
Temperature: