



Firma: G Store & Repair doo  
Adresa: Bul.Mihajla Pupina 10z/3  
Telefon: 011 785 66 66  
Fax:  
PIB: 112029009  
E-mail: [office@gstore.rs](mailto:office@gstore.rs)

---

Supermicro X10SDV-F-O Intel Xeon D-1540 DDR4  
SATA3&USB3.0 2GbE Mini-ITX Motherboard & CPU  
Combo ( X10SDV-F )

---

Šifra: 83862

Kategorija proizvoda: Dodatna oprema za server

Proizvođač: SUPERMIKRO



**Cena: 117.880 rsd.**

**Intel Xeon Processor D-1541**

|  |  |
|--|--|
| CPU:   | Intel Xeon Processor D-1541  |
| CPU Core Quantity:                                     | 8  |
| CPU Socket Standard:                                   | Socket 1667  |
| Internal Clock Rate:                                   | 2.1 GHz  |
| CPU Installed Quantity:                                | 1  |
| Max. CPU Bus Clock Rate:                               | 2.7 GTsec  |
| Installed L2 Cache Memory<br>Storage Capacity:         | 2 MB   |
| Installed L3 Cache Memory<br>Storage Capacity:         | 12 MB  |
| CPU Maximum Quantity Supports:                         | 1  |
| Features:  | Supports 14nm Processors   |
| Memory Type:   | DDR4 SDRAM   |
| Provides Error Checking Method:                        | ECCNon-ECC<br>2133MHz(PC4-17000)<br>1866MHz(PC4-14900)<br>1600MHz(PC4-12800)<br>2400MHz(PC4-19200) |
| Memory Speed:  | 2400MHz(PC4-19200)   |
| Memory Form Factor:                                    | DIMM 288-pin   |
| Maximum Installable System<br>Memory Storage Capacity: | 128 GB   |
| Memory Slot Total Quantity:                            | 4  |
| Memory Features:                                       | Registered<br>Unbuffered   |
| Storage Controller Type:                               | SATA III   |
| RAID Controller Interface Type:                        | SATA III<br>Level 0<br>Level 1<br>Level 10   |
| Supports RAID Level:                                   | Level 5  |
| Video Controller Integrated:                           | yes  |
| Video Chipset:   | Aspeed AST2400   |
| LAN Integrated:  | yes  |
| LAN Chipset:   | Intel i350-AM2<br>Gigabit EthernetFast<br>EthernetEthernet   |
| Data Link Protocol Supports:                           | EthernetEthernet   |
| PCI Express 3.0 x16 Slot<br>Quantity:                  | 1  |
| M.2 Slot Quantity:                                     | 1  |
| SATA III:  | 6  |
| LAN:   | 2 (RJ-45)  |
| USB3.0:  | 2 (USB 3.0 (type A))   |